



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Berutemp PA 415 GR**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Lubricant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

CARL BECHEM GMBH
Weststraße 120
58089 Hagen, Germany
Phone +49 2331 935-0
Fax +49 2331 935-1199
Email: bechem@bechem.de
http://www.bechem.com

Informing department: product safety department : ps@bechem.com

1.4 Emergency telephone number: +49 2331 935-1500

Code: 6005529

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GHS regulation.

Hazard pictograms Void

Signal word Void

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixture

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 128-37-0	2,6-di-tert-butyl-p-cresol	N R50/53	< 1.0%
EINECS: 204-881-4		Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

Additional information For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air.

After skin contact Wash with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Seek medical treatment.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Trade name: **Berutemp PA 415 GR**

(Contd. of page 1)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

Carbonmonoxide (CO) and carbon dioxide (CO₂)

Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.

6.3 Methods and material for containment and cleaning up:

Collect mechanically.

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling No special measures required.

Information about protection against explosions and fires: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: Store only in the original container.

Information about storage in one common storage facility: Do not store together with oxidising and acidic materials.

Further information about storage conditions:

Recommended storage temperature: room temperature

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to when handling the lubricant.

Breathing equipment: Not required.

Protection of hands: Protective gloves.

Material of gloves Nitrile rubber, NBR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not suitable are gloves made of the following materials:

Leather gloves

Strong gloves

Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Viscous

Colour: Black

Smell: Mineral-oil-like

Change in condition

Melting point/Melting range: Not determined

(Contd. on page 3)

Trade name: **Berutemp PA 415 GR**

(Contd. of page 3)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This data is based on our present knowledge. However, it shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Department issuing data specification sheet: product safety department**Contact:** ps@bechem.com**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

*** Data compared to the previous version altered.**