





## **NO-TOX<sup>®</sup> FOOD GRADE WATERPROOF CHAIN LUBRICANT**

**No-Tox Food Grade Waterproof Chain Lubricant**, commonly known as No-Tox Waterproof Chain Lube, is a tacky and waterproof chain lubricant and is NSF H1 registered for use where incidental food contact may occur. **No-Tox Food Grade Waterproof Chain Lubricant** is recommended for most unheated chain applications found in the "clean" industries such as food, beverage, pharmaceutical and personal care products. It is fortified with proprietary anti-wear agents and other additives that promote penetration and lubrication of sprockets, links, pins and bushings. **No-Tox Food Grade Waterproof Chain Lubricant** also contains rust and corrosion inhibitors and special polymers to resist flinging and dripping.

### **Applications**

• Widely used in food and poultry plants operating under the Federal Meat and Poultry Products Inspection Program's Food Safety and Inspection Service (FSIS)

### Features and Benefits

1 0	I cuiares una Denejus			
٠	NSF H1 registered	Use where incidental food contact may occur.		
٠	Compliances	Kosher and Pareve approved. Halal certified.		
•	Bacteriological protection	Effectively inhibits the growth of certain bacteria, yeast and mold in the lubricant.		
٠	Anti-wear protection	Reduces friction and wear.		
٠	Rust and oxidation prevention	Longer service life.		
٠	Tacky and non-drip	Provides superior adhesion to metal.		

### **General Description**

**No-Tox Food Grade Waterproof Chain Lubricant** is blended to give outstanding anti-wear and rust protection. The convenient aerosol container sprays the unique formulation on the chain protecting against rust and metal-to-metal contact. **No-Tox Food Grade Waterproof Chain Lubricant**, formulated with the highest quality ingredients, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified. **No-Tox Food Grade Waterproof Chain Lubricant** is available in bulk and spray aerosol forms.

### Product No. 64060, 64070

Page 1 of 2

1/3/2012

With continual research and development, Bel-Ray Company, Inc. reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.

Bel-Ray Company, Inc. • P.O. Box 526 • Farmingdale, NJ 07727 USA TEL +1 732-938-2421 • FAX +1 732-938-4232 • www.belray.com

# NO-TOX<sup>®</sup> FOOD GRADE WATERPROOF CHAIN LUBRICANT <u>TYPICAL PROPERTIES</u>

<u>Product No.</u>	<u>64060</u>	<u>64070</u>
	Bulk	Spray
ISO Viscosity Grade	460	
Viscosity, ASTM D445 @ 40°C, cSt @ 100°C, cSt	466 36.8	
Rust Test, ASTM D665, Procedure A & B	Pass	
Falex EP Test, ASTM D3233 Method B Non-seizure Load, lbf	1250	
Color	Pale Yellow	White Foam

Aerosol Caution: Use in a well-ventilated space.

Product is flammable and should be used with appropriate caution. Do not spray on a hot surface or in proximity to flames or open fire. Do not puncture or incinerate container, even when empty. Always wear safety glasses when using this product. Keep container away from heat.

Page 2 of 2

With continual research and development, Bel-Ray Company, Inc. reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.

Bel-Ray Company, Inc. • P.O. Box 526 • Farmingdale, NJ 07727 USA TEL +1 732-938-2421 • FAX +1 732-938-4232 • www.belray.com