SAFETY DATA SHEET



Energrease LC 2-T

Section 1. Identification

GHS product identifier Energrease LC 2-T Product code 460862-AUXX

SDS no. 460862

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Grease for industrial applications.

mixture For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Manufacturer

Supplier BP Australia Pty Ltd

Level 17, 717 Bourke Street Docklands, Victoria 3008 ABN 53 004 085 616 www.bp.com.au

Tel: +61 (03) 9268 4111 Fax: +61 (03) 9268 3321

EMERGENCY TELEPHONE

NUMBER

+61 2801 44558 (or 1800 14 14 74 within Australia)

OTHER PRODUCT INFORMATION

Technical Helpline Number: 1300 139 700

Section 2. Hazard(s) identification

Classification of the substance or mixture

Not classified.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Supplemental label elements

Other hazards which do not

Defatting to the skin.

result in classification

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure

constitute a major medical emergency.

See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data

Sheet.

Product name Energrease LC 2-T Product code 460862-AUXX Page: 1/9

Version 1 Date of issue 11/01/2016 Format Australia Language ENGLISH

Section 3. Composition and ingredient information

Substance/mixture

Mixture

Highly refined base oil and additives. Thickening agent.

Ingredient name% (w/w)CAS numberBase oil - unspecified≥90Varies - See Key to abbreviations

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing.

Check for and remove any contact lenses. Get medical attention.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

Remove contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical

attention if symptoms occur.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with

extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the

product considerable distances along tissue planes.

Specific treatments No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide

extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet.

Specific hazards arising

from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

Combustion products may include the following: carbon dioxide

carbon monoxide metal oxide/oxides

Product name Energrease LC 2-T

Product code 460862-AUXX Page: 2/9

Version 1 Date of issue 11/01/2016

Format Australia Language ENGLISH

Section 5. Fire-fighting measures

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures
Advice on general
occupational hygiene

Put on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 45°C (113°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Product name Energrease LC 2-T Product code 460862-AUXX Page: 3/9

Version 1 Date of issue 11/01/2016 Format Australia Language ENGLISH

(Australia) (ENGLISH)

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
Base oil - unspecified	Safe Work Australia (Australia). TWA: 5 mg/m³ 8 hours. Form: Oil mist, mineral	

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection **Hand protection**

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons

and/or impervious chemical suits and boots will be required.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection

Version 1

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Product name Energrease LC 2-T

Date of issue 11/01/2016

Product code 460862-AUXX Page: 4/9

Format Australia Language ENGLISH

(Australia)

(ENGLISH)

Section 8. Exposure controls and personal protection

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Refer to standards: Respiratory protection: AS/NZS 1715 and AS/NZS 1716

Gloves: AS/NZS 2161.1

Eye protection: AS/NZS 1336 and AS/NZS 1337

Section 9. Physical and chemical properties

Appearance

Physical state
Colour
Grease
Green. Blue.
Odour
Not available.
Odour threshold
Not available.
PH
Not available.
Melting point
Not available.
Not available.
Not available.
Not available.

Flash point Closed cup: >250°C (>482°F) [Estimated. Based on Lubricants - Base Oils]

Evaporation rate Not available.

Flammability (solid, gas) Not applicable. Based on - Physical state

Lower and upper explosive

(flammable) limits

Not available.

Vapour pressure Not available.
Vapour density Not available.

Relative density <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility
Partition coefficient: n-

octanol/water

Not available.

insoluble in water.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not

occur.

Conditions to avoid No specific data.

Incompatible materials Reactive or incompatible with the following materials: reducing materials.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Product name Energrease LC 2-T Product code 460862-AUXX Page: 5/9

Version 1 Date of issue 11/01/2016 Format Australia Language ENGLISH

Section 11. Toxicological information

Information on toxicological effects

Information on the likely

routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact No known significant effects or critical hazards.

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

No known significant effects or critical hazards. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

No specific data. Eye contact Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

> irritation dryness cracking

No specific data. Ingestion

Delayed and immediate effects and also chronic effects from short and long term exposure

Potential risk of transient stinging or redness if accidental eye contact occurs. Eye contact Inhalation

Inhalation of oil mist or vapours at elevated temperatures may cause respiratory

irritation.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

General No known significant effects or critical hazards. Carcinogenicity No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. No known significant effects or critical hazards. **Teratogenicity Developmental effects** No known significant effects or critical hazards. **Fertility effects** No known significant effects or critical hazards.

Section 12. Ecological information

Persistence and degradability

Not available.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Soil/water partition Not available.

coefficient (Koc)

Mobility Spillages are unlikely to penetrate the soil.

Product name Energrease LC 2-T Product code 460862-AUXX Page: 6/9

Language ENGLISH Version 1 Date of issue 11/01/2016 **Format Australia**

Section 12. Ecological information

Other ecological information

Spills are unlikely to form a distinct film on the water surface, and may become dispersed as globules if mixed or agitated.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Special Precautions for Landfill or Incineration No additional special precautions identified.

Section 14. Transport information

	ADG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user Not available.

Section 15. Regulatory information

Standard Uniform Schedule of Medicine and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

International lists
National inventory

REACH Status For the REACH status of this product please consult your company contact, as

identified in Section 1.

Australia inventory (AICS)

Canada inventory

All components are listed or exempted.

Product name Energrease LC 2-T Product code 460862-AUXX Page: 7/9

Version 1 Date of issue 11/01/2016 Format Australia Language ENGLISH

(Australia)

(ENGLISH)

Section 15. Regulatory information

Japan inventory (ENCS)

Korea inventory (KECI)

All components are listed or exempted.

All components are listed or exempted.

All components are listed or exempted.

Taiwan inventory (CSNN)

United States inventory

All components are listed or exempted.
All components are listed or exempted.

(TSCA 8b)

(PICCS)

Section 16. Any other relevant information

History

Date of printing 11/01/2016

Date of issue/Date of 11/01/2016

revision

Date of previous issue No previous validation

Version

Product Stewardship

Key to abbreviations ADG = Australian Dangerous Goods

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NOHSC = National Occupational Health and Safety Commission

STEL = Short term exposure limit

SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

TWA = Time weighted average VOC = Volatile Organic Compound

SADT = Self-Accelerating Decomposition Temperature

Varies = may contain one or more of the following 101316-69-2, 101316-70-5, 101316-71-6, 101316-72-7, 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-64-9, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1, 74869-22-0, 90669-74-2

Procedure used to derive the classification

Classification	Justification
Not classified.	

✓ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the

Product name Energrease LC 2-T Product code 460862-AUXX Page: 8/9

Version 1 Date of issue 11/01/2016 Format Australia Language ENGLISH

Section 16. Any other relevant information

material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Energrease LC 2-T Product code 460862-AUXX Page: 9/9

Version 1 Date of issue 11/01/2016 Format Australia Language ENGLISH (Australia) (ENGLISH)