

Product Information

MOVING YOUR WORLD



CASSIDA CHAIN OIL 150

Synthetic chain lubricant for food and beverage processing equipment

Performance Features

- Excellent adhesive properties minimise 'fling-off' in use and wash-off by both cold and hot water
- Extends the service life of chains and reduce down-time due to superior wear prevention and corrosion protection, even under wet or aggressive conditions
- Easily applied by either brush, through baths or by automatic lubrication system
- Neutral odour and taste
- Solvent-free formulation to provide greater safety in use



Chains



High temperature



Low temperature



Partner Programme



NSF registered

Certifications and Specifications

- NSF H1
- NSF ISO 21469
- Kosher
- Halal

Description

CASSIDA CHAIN OIL 150 is a fully synthetic high performance, anti-wear chain oil which have been specially developed for use in machinery used in the food and beverage processing and packaging industry. It is based on a careful blend of synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food industry. Certified by NSF for ISO 21469 and registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good

CASSIDA CHAIN OIL 150 | 1000774 | 2022-08-12 | 1 / 5

Product Information

MOVING YOUR WORLD



Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

Applications

- Drive and transport chains in the food industry
- Also intended for use in equipment manufacturing food packaging

Seal and Paint Compatibility

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

Handling and Storage

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend to use the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 5 years of date of manufacture, whichever is the sooner).

Technical Data: CASSIDA CHAIN OIL 150

Characteristics	Value	Unit	Test Method
NSF Reg. No.	144683		
Color	Colourless to pale yellow		
Density [+15 °C]	846	kg/m ³	ISO 12185
Flashpoint	260	° C	ISO 2592
Pourpoint	-54	° C	ISO 3016
Kin. Visc. [+40 °C]	150	mm ² /s	ISO 3104
Kin. Visc. [+100 °C]	19	mm ² /s	ISO 3104
Operating temperatures	-30 to +140	° C	LV0124
short-term peak	+150	° C	

LV = Laboratory Specification
Typical for current production. Variations in these characteristics may occur.

Product Information

MOVING YOUR WORLD



As far as we know this information reflects the current state of knowledge and our research. It cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check their suitability and be satisfied that the output will be satisfactory. Please be aware that our products must not be used for applications in nuclear primary circuits or on-board aerospace systems. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without prior announcement, unless otherwise provided in customer-specific agreements. With the publication of this product information sheet, all previous editions cease to be valid.

We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRICANTS GERMANY provides service and individual advice. Please contact us!
E-Mail: zentrale-flg@fuchs.com