


CASSIDA CHAIN OIL HTE

Product Information

Synthetic high temperature chain lubricant for food and beverage processing equipment



CASSIDA CHAIN OIL HTE is a synthetic, high performance ester based oil which has been specially formulated for the food industry to lubricate drive and transport chains at elevated temperatures.

It is based on an advanced blend of synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food and beverage industry.

Certified by NSF for ISO 21469 and registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

CERTIFICATIONS AND SPECIFICATIONS

- NSF H1
- NSF ISO 21469
- Kosher
- Halal



PERFORMANCE FEATURES

- Thermal stability up to +240 °C
- Low evaporation loss
- Excellent corrosion resistance
- Medium viscosity for easy application
- Excellent adhesive properties minimize "fling-off" in use and wash-off by both cold and hot water
- Easily applied by either brush, through baths or by automatic lubrication systems
- Neutral odour and taste
- Solvent-free formulation to provide greater safety in use

APPLICATIONS

- Drive and transport chains in the food industry
- Also intended for use in equipment for manufacturing food packaging

SEAL AND PAINT COMPATIBILITY

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

HANDLING AND STORAGE

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend to use the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 5 years of date of manufacture, whichever is the sooner).

TYPICAL CHARACTERISTICS (Typical for current production. Variations in these characteristics may occur.)

			CASSIDA CHAIN OIL HTE
Property	Test Method		
NSF Reg. No.			144680
Colour			Yellowish
Density at +15 °C	kg/m ³	DIN 51757	918
Flashpoint	°C	ISO 2592	>250
Pourpoint	°C	ISO 3016	<-30
Kin. Visc. at +40 °C	mm ² /s	ISO 3104	230
Kin. Visc. at +100 °C	mm ² /s	ISO 3104	21
Viscosity Index	ISO 2909		106
Operating temperatures	°C	LLV 134*	-25 to +240

* Lubritech Laboratory Method



FUCHS LUBRITECH GMBH
Werner-Heisenberg-Straße 1
67661 Kaiserslautern / Germany
Tel. +49 (0) 6301 3206-0
Fax +49 (0) 6301 3206-940
www.fuchs-lubritech.com

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us! E-Mail: cassida.lubricants@fuchs-lubritech.de