

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: RENOLIT UNIWAY LIX 42 PA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricating grease

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS SWEDEN AB
Vitsåvägen 3
137 41 Västerhaninge
Sweden
Telephone: +46 8 128 25 000

Contact Person: HSE Advisor
E-mail: fse-hseasc@fuchs.com
Telephone: +46 8 128 25 000

1.4 Emergency telephone number: +46 20 996 000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has not been classified as hazardous, but needs to be labelled according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

Hazard summary

Physical Hazards: No data available.

2.2 Label Elements

EUH208: Contains bismuth salts. May produce an allergic reaction.

EUH210: Safety data sheet available on request.

2.3 Information on other hazards

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept.

Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Product name: RENOLIT UNIWAY LIX 42 PA

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Lubricating grease: Thickener system and additives in synthetic base oil.

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
Dilithium azelate	EINECS: 254-184-4	1,00% - <5,00%	01-2120119814-57	
bismuth salts	EINECS: 288-470-5	1,00% - <5,00%	01-2120769500-56	
Amine aromatic , alkylated	EINECS: 270-128-1	0,10% - <1,00%	01-2119491299-23	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification
Dilithium azelate	EINECS: 254-184-4	CLP: Acute Tox. 4;H302
bismuth salts	EINECS: 288-470-5	CLP: Skin Sens. 1;H317, Eye Irrit. 2;H319
Amine aromatic , alkylated	EINECS: 270-128-1	CLP: Repr. 2;H361f, Aquatic Chronic 3;H412

CLP: Regulation No. 1272/2008.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

Product name: RENOLIT UNIWAY LIX 42 PA

5.2 Special hazards arising from the substance or mixture:

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire-fighting procedures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Not required.

6.2 Environmental Precautions:

Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Provide adequate ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products.

7.2 Conditions for safe storage, including any incompatibilities:

Store in original tightly closed container. Keep separate from food, feedstuffs, fertilizers and other sensitive material. Store away from incompatible materials. No special precautions necessary if used correctly. Use only containers specifically permitted for this substance/product. Protect from contamination

7.3 Specific end use(s):

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

8.2 Exposure controls

Product name: RENOLIT UNIWAY LIX 42 PA

Appropriate engineering controls: Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eyeface protection: Safety glasses (EN 166) recommended during refilling. Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand Protection:

Material: Nitrile butyl rubber (NBR).
Min. Breakthrough time: ≥ 480 min
Recommended thickness of the material: $\geq 0,38$ mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other: Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection: Not relevant, due to the form of the product.

Thermal hazards: Not known.

Hygiene measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls: No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Beige
Odor:	Characteristic
pH:	substance/mixture is non-soluble (in water) Not applicable
Drop Point:	not determined
Boiling Point:	not determined

Product name: RENOLIT UNIWAY LIX 42 PA

Flash Point:	> 150 °C
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	not determined
Flammability Limit - Upper (%)—:	Not applicable for mixtures
Flammability Limit - Lower (%)—:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	< 1,00 g/cm ³ (25 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	not determined
Decomposition Temperature:	not determined
Kinematic viscosity:	> 20,5 mm ² /s (40 °C)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
Particle characteristics:	Study technically not feasible
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Oral

Product:	ATEmix: 3.635 mg/kg ATEmix: 40.816,33 mg/kg
-----------------	--

Product name: RENOLIT UNIWAY LIX 42 PA

Specified substance(s)

Dilithium azelate LD 50 (Rat): 2.000 mg/kg (OECD 420)

Amine aromatic , alkylated LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product:

Specified substance(s)

Dilithium azelate OECD 431
Based on available data, the classification criteria are not met.
OECD 439
Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation:

Product:

Specified substance(s)

Dilithium azelate OECD 405 (Rabbit):
Based on available data, the classification criteria are not met.

Amine aromatic , alkylated OECD 405 (Rabbit):
Not irritant.

Respiratory or Skin Sensitization:

Product:

Experimental data has shown that the concentration of potentially sensitizing components present in this product does not induce skin sensitization (OECD 429).

Specified substance(s)

Dilithium azelate , OECD 429 (Mouse)
Based on available data, the classification criteria are not met.

Amine aromatic , alkylated No sensitizing effect (guinea pig); OECD 406

Germ Cell Mutagenicity

Product:

In vitro

Specified substance(s)

Dilithium azelate (OECD 471)
Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Reproductive toxicity

Product:

Product name: RENOLIT UNIWAY LIX 42 PA

Specific Target Organ Toxicity - Single Exposure

Product:

Specific Target Organ Toxicity - Repeated Exposure

Product:

Aspiration Hazard

Product:

11.2 Information on other hazards

Endocrine disrupting properties

Product:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product:

Fish

Specified substance(s)

Dilithium azelate LC 50 (Fish, 96 h): 100 mg/l (OECD 203)

Amine aromatic , alkylated LC 50 (Fish, 96 h): > 100 mg/l (OECD 203)

Aquatic Invertebrates

Specified substance(s)

Dilithium azelate EC 50 (Water Flea, 48 h): 100 mg/l (OECD 202)

Amine aromatic , alkylated EC 50 (Daphnia magna): 51 mg/l (OECD 202)

Chronic Toxicity

Product:

Toxicity to Aquatic Plants

Specified substance(s)

Dilithium azelate EC 50 (Alga, 72 h): 100 mg/l (OECD 201)

Amine aromatic , alkylated EC 50 (72 h): > 100 mg/l (OECD 201)

12.2 Persistence and Degradability

Biodegradation

Product:

Not applicable for mixtures

Product name: RENOLIT UNIWAY LIX 42 PA

Specified substance(s)

Dilithium azelate (OECD 301D) Inherently biodegradable

Amine aromatic , alkylated Not readily degradable.

12.3 Bioaccumulative potential

Product: Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Endocrine disrupting properties

Product: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects: No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

European Waste Codes

12 01 12*: spent waxes and fats

SECTION 14: Transport information

ADR/RID

- 14.1 UN number or ID number: —
14.2 UN Proper Shipping Name: —
14.3 Transport Hazard Class(es)
Class: Non-dangerous goods
Label(s): —
Hazard No. (ADR): —
Tunnel restriction code: —
14.4 Packing Group: —
14.5 Environmental hazards: —
14.6 Special precautions for user: —

Product name: RENOLIT UNIWAY LIX 42 PA

IMDG

- 14.1 UN number or ID number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
 - Class: Non-dangerous goods
 - Label(s): —
 - EmS No.: —
- 14.3 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

IATA

- 14.1 UN number or ID number: —
- 14.2 Proper Shipping Name: —
- 14.3 Transport Hazard Class(es):
 - Class: Non-dangerous goods
 - Label(s): —
- 14.4 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

14.7 Maritime transport in bulk according to IMO instruments: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. Regulation 1005/2009/EC on substances that deplete the ozone layer, Annex I, Controlled Substances: none

EU. Regulation 2019/1021/EU on persistent organic pollutants (POPs) (recast), as amended: none

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

DIRECTIVE 2012/18/EU (SEVESO III) on the control of major-accident hazards involving dangerous substances

Not applicable

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H361f Suspected of damaging fertility.
- H412 Harmful to aquatic life with long lasting effects.

Other information: The classification complies with the current EU lists; however, it has been

Product name: RENOLIT UNIWAY LIX 42 PA

supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: - On the basis of test data - Calculation Method - Bridging Principle "Substantially similar mixtures" - Expert Judgement

Revision Date:

20.12.2022

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.