




# **HAYNES<sup>®</sup>** **PRODUCT INFORMATION**

THE WORLD'S LEADING MANUFACTURER OF PREMIUM FOOD GRADE LUBRICANTS



## **HAYNES LUBRI-FILM**

**Heavy Duty Lubricating Grease**  
**4oz Tubes, 11.25oz Sprays,**  
**12 oz Cartridges, and Bulk Containers**  
**NSF rated H1**



**Haynes Lubri-Film** is a heavy duty sanitary lubricant with high load bearing, low friction properties. This lubricant is authorized by the NSF (rated H1) for use in food processing plants for incidental food contact. All ingredients are FDA approved.

**Haynes Lubri-Film** provides a protective coating to all metal parts. A thin film will retain effectiveness on bearings, slides, and other lubricated surfaces despite moisture. By staying on the work area, corrosion of metal is minimized. This sanitary lubricant is highly resistant to separation or bleed. It will not dry or gum on your equipment.

### **COMMON APPLICATIONS:**

- o **POSITIVE PUMPS**
- o **HOMOGENIZER PISTONS**
- o **SIZE REDUCTION EQUIPMENT**
- o **PLUG VALVES**
- o **DISPENSING UNITS**
- o **CENTRALIZED LUBRICATION EQUIPMENT**
- o **BEVERAGE EQUIPMENT**
- o **FREEZERS**
- o **STAINLESS STEEL THREADS**
- o **SEPARATORS**
- o **CLARIFIER**

## **TECHNICAL DATA INFORMATION**

<i>TEST</i>	<i>ASTM Method</i>	<i>Typical Test Results</i>
<b>Melt Point</b>	<b>D566</b>	<b>200°F</b>
<b>Consistency</b>	<b>D217</b>	<b>333</b>
<b>Viscosity(Saybolt @ 210°F )</b>	<b>D445</b>	<b>55</b>
<b>Viscosity(CST @ 100°C)</b>	<b>D2161</b>	<b>8</b>
<b>Four Ball Wear Scar Diameter, mm</b>	<b>D2266</b>	<b>0.63</b>
<b>Operating Range, Min °F, Max °F</b>		<b>-15° - 210°F</b>
<b>NLGI</b>		<b>1</b>

**Haynes Manufacturing Company 24142 Detroit Road Westlake, Ohio 44145**  
**U.S.A. & Canada: 1-800-992-2166 Phone: 440-871-2188 Fax: 440-871-0855**  
**<http://www.haynesmfg.com>**