

## Technical Data Sheet

# Interflon Food Grease HD00

### Semi-fluid grease for industrial gearboxes

Semi-fluid EP grease designed to lubricate industrial gearboxes and machine parts with automatic grease and oil delivery systems. With the fluidity to flow like oil while having more “body” at operating temperature to provide considerably less friction. Resists leaking through worn seals often found in older gearboxes. Reduces power consumption in gearboxes and allows to safely extending oil change intervals. Formulated with MicPol® Technology, which forms a durable lubrication film capable of reducing friction and wear much better than conventional oils and greases.

Interflon Food Grease HD00 is listed by the NSF for the use in applications with incidental food contact.

### Applications

Applications include the lubrication of industrial gearboxes running at slow to moderately speed and machine parts such as bearings, chains and slides with automatic grease and oil delivery systems.

### Advantages

- ⦿ Excellent, long-lasting reduction of friction and wear
- ⦿ Reduces oil temperature and power consumption
- ⦿ Much longer lubricant life
- ⦿ Reduced gearbox leakage
- ⦿ Outstanding shear stability
- ⦿ High level of rust and corrosion protection

### Instructions for use

For best results, parts should be cleaned or purged of the previous lubricant prior to use. Drain the old oil from the gearbox as prescribed by the manufacturer. When used in central lubrication systems remove any filters. Drain the old oil from the gearbox as prescribed by the manufacturer. For application in gearboxes please consult your Technical Advisor for the correct filling level.

Property	Result	Method
Composition	Mixture of mineral and synthetic oils, thickener, additives and MicPol®.	
Colour	Light brown	
Density 20°C	0.90 g/cm <sup>3</sup>	
Lowest application temperature	-25°C (for applications in gearboxes: 0°C )	
Highest application temperature	145°C	
Manufacturing date	The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing.	
Shelf life*	4 years	
Base oil viscosity 40°C	165 cSt	ASTM D445
Dn factor	350000	
Grease code	KPF00N-25	DIN 51825
NLGI grade	00	ASTM D217
SKF Emcor salt water	0-0	DIN 51802
NSF registration number	147480	
NSF	H1	
ISO 21469	Yes	
Halal	Yes	
Kosher	Yes	
Thickener	Calcium sulfonate	

\* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.