

Trade name :	F.EE Haftschmierstoff für offene A	F.EE Haftschmierstoff für offene Antriebe - ArtNr. 1788818		
<b>Revision date :</b>	23.11.2023	Version (Revision) :	3.2.0 (3.1.0)	
Print date :	07.12.2023			

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier F.EE Haftschmierstoff für offene Antriebe - Art.-Nr. 1788818 1.2 Relevant identified uses of the substance or mixture and uses advised against **Relevant identified uses** Product Categories [PC] PC24 - Lubricants, greases, release products 1.3 Details of the supplier of the safety data sheet Supplier (manufacturer/importer/only representative/downstream user/distributor) Lubricant Consult GmbH Street : Gutenbergstraße 13 **Postal code/city :** 63477 MAINTAL (GERMANY) Telephone: +49 6109/7650-0 Telefax : +49 6109/7650-51 E-mail: msds-request@lubcon.com Information contact : Environment, Health & Safety: Dr. Rüdiger Hofmann **1.4 Emergency telephone number** +49 6109/7650-0 Monday to Friday 8:00 AM to 4:00 PM (CET)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP] None

### 2.2 Label elements

```
Labelling according to Regulation (EC) No. 1272/2008 [CLP]
Special rules for supplemental label elements for certain mixtures
 EUH210
```

Safety data sheet available on request.

### 2.3 Other hazards

None

### **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

### **Hazardous ingredients**

Dilithium azelate ; REACH registration No. : 01-2120119814-57-xxxx ; EC No. : 254-184-4; CAS No. : 38900-29-7 Weight fraction :

≥ 1 - < 5 % Classification 1272/2008 [CLP] :

Acute Tox. 4 ; H302

#### Further ingredients

Distillates (petroleum), hydrotreated heavy naphthenic ; REACH registration No. : 01-2119467170-45-xxxx ; EC No. : 265-155-0; CAS No. : 64742-52-5

Weight fraction :

≥ 50 - < 100 %

Metallic soap

Page : 1 / 7



Trade name : Revision date : Print date : F.EE Haftschmierstoff für offene Antriebe - Art.-Nr. 1788818 23.11.2023 Version (Revision) : 07.12.2023

3.2.0 (3.1.0)

Additives not to declare

#### Additional information

The following applies to complex mineral oil distillates listed under "Further ingredients": Nota L, DMSO extract according to IP 346 < 3%.

Full text of H- and EUH-phrases: see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

#### **General information**

When in doubt or if symptoms are observed, get medical advice.

### **Following inhalation**

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

### In case of skin contact

Remove contaminated, saturated clothing immediately. Wash immediately with: Water and soap In case of skin irritation, consult a physician.

#### After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Let water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell.

### **4.2 Most important symptoms and effects, both acute and delayed** No information available.

## 4.3 Indication of any immediate medical attention and special treatment needed None

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

### Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO2). ABC-powder. BC-powder. Foam. Dry sand.

### Unsuitable extinguishing media

Water. Strong water jet. High power water jet.

5.2 Special hazards arising from the substance or mixture Hazardous combustion products: Carbon monoxide (CO). Carbon dioxide (CO2). Burning produces heavy smoke.

### 5.3 Advice for firefighters

Use suitable breathing apparatus. **5.4** Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

Special danger of slipping by leaking/spilling product.

### 6.1 Personal precautions, protective equipment and emergency procedures

Page : 2 / 7



Trade name :	F.EE Haftschmierstoff für offene	F.EE Haftschmierstoff für offene Antriebe - ArtNr. 1788818		
Revision date :	23.11.2023	Version (Revision) :	3.2.0 (3.1.0)	
Print date :	07.12.2023			

None

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Ensure waste is collected and contained. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

### 6.3 Methods and material for containment and cleaning up

Take up mechanically, placing in appropriate containers for disposal. Soak up inert absorbent and dispose as waste requiring special attention. Suitable material for taking up: Universal binder. Kieselguhr.

### 6.4 Reference to other sections

None

### **SECTION 7: Handling and storage**



### 7.1 Precautions for safe handling

### **Protective measures**

It is recommended to design all work processes always so that the following is excluded: Generation/formation of mist. Avoid: Inhalation of vapours or spray/mists. Skin contact, Eye contact. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

### 7.2 Conditions for safe storage, including any incompatibilities

### Hints on joint storage

Storage class: 11

Storage class (TRGS 510): 11

Keep away from

Food and feedingstuffs

### Further information on storage conditions

Keep/Store only in original container. Keep container tightly closed. Protect against UV-radiation/sunlight. Humidity. Contact with air/oxygen. Dust deposits.

### 7.3 Specific end use(s)

None

### **SECTION 8: Exposure controls/personal protection**

Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and after work. Take the precautions customary when handling chemicals. Change contaminated, saturated clothing. Keep away from sources of ignition - No smoking.

### 8.1 Control parameters

None

### 8.2 Exposure controls

### Personal protection equipment

Eye/face protection

Eye protection: not required. Avoid: Eye contact.

Recommended eye protection articles DIN EN 166

Skin protection Hand protection



Trade name :	F.EE Haftschmierstoff für offene Antriebe - ArtNr. 1788818		
Revision date :	23.11.2023	Version (Revision) :	3.2.0 (3.1.0)
Print date :	07.12.2023		

Hand protection is not required **By long-term hand contact**: Wear suitable gloves. **Suitable material**: PE (Polyethylene). NR (natural rubber, natural latex). NBR (Nitrile rubber). **Breakthrough time (maximum wearing time)**: PE < 30 min.; NR < 10 min.; NBR > 480 min. **Thickness of the glove material**: min. 0,38 mm **Recommended glove articles**: EN ISO 374; DIN EN 420 Uvex. KCL, MAPA. Or comparable articles from other companies.

### Respiratory protection

No special measures are necessary. Avoid: Inhalation of vapours or spray/mists

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Colour: dark brown

Safety rele	evant l	basis d	lata
-------------	---------	---------	------

Physical state :			pasty	
Initial boiling point and boiling range :	(1013 hPa)	>	300 °C	2
Decomposition temperature :	(1013 hPa)	>	220 °C	2
Flash point :	(1013 hPa)	>	220 °C	2
Vapour pressure :	( 50 °C )	<	0,1 hł	Pa
Density :	( 20 °C )	=	0,95 g/	/cm³
9.2 Other information				

None

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

The product is stable.

#### **10.3 Possibility of hazardous reactions** No information available.

10.4 Conditions to avoid

### No information available.

**10.5 Incompatible materials** Oxidising agent, strong.

### 10.6 Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2). Gases/vapours, harmful.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute effects**

By analogy:	
Acute oral toxicity	
Parameter :	LD50
Exposure route :	Oral



Trade name :	F.EE Haftschmierstoff für offene Antriebe - ArtNr. 1788818		
Revision date :	23.11.2023	Version (Revision) :	3.2.0 (3.1.0)
Print date :	07.12.2023		

Species :	Rat
Effective dose :	> 4000 mg/kg
Parameter :	LD50 (Dilithium azelate ; CAS No. : 38900-29-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 300 mg/kg
Acute dermal toxicity	
Parameter :	LD50
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2500 mg/kg
Parameter :	LD50 (Dilithium azelate ; CAS No. : 38900-29-7)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg

### 11.2 Information on other hazards

No information available.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

No information available.

### 12.2 Persistence and degradability

### **Biodegradation**

Overall evaluation on the mixture: Not readily biodegradable (according to OECD criteria).

#### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### **12.6 Endocrine disrupting properties**

Endocrine disrupting potential: None known.

### 12.7 Other adverse effects

This product does not contain nanoparticles.

### 12.8 Overall evaluation

If product enters soil, it will be mobile and may contaminate groundwater. In accordance with the required stability the product is poorly biodegradable.

### SECTION 13: Disposal considerations

Dispose according to legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### 13.1 Waste treatment methods

Send to a hazardous waste incinerator facility under observation of official regulations. Collect the waste separately. Evidence for disposal must be provided.

### Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Waste code product



Trade name :	F.EE Haftschmierstoff für offen	F.EE Haftschmierstoff für offene Antriebe - ArtNr. 1788818		
Revision date :	23.11.2023	Version (Revision) :	3.2.0 (3.1.0)	
Print date :	07.12.2023			

12 01 12 - Spent waxes and fats

#### Waste code packaging

15 01 10 - Packaging containing residues of or contaminated by hazardous substances. - Dispose of completely emptied containers as combustible waste or metal waste depending on the material.

### **SECTION 14: Transport information**

### 14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es) No dangerous good in sense of these transport regulations.

### 14.4 Packing group

No dangerous good in sense of these transport regulations.

### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

### 14.6 Special precautions for user

None

### **14.7 Maritime transport in bulk according to IMO instruments** No transport as bulk according to IBC Code.

### **SECTION 15: Regulatory information**

# <sup>15.1</sup> Safety, health and environmental regulations/legislation specific for the substance or mixture

### National regulations

Restrictions of occupation

#### Not relevant

Störfallverordnung

Not subject to StörfallVO.

#### Water hazard class (WGK)

Class: 1 (Slightly hazardous to water) Classification according to AwSV

#### Other regulations, restrictions and prohibition regulations

General Water Assessment Methodology (ABM) of the Netherlands: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Switzerland

#### **VOCV-Regulation**

Volatile organic compounds (VOC) content in percent by weight : 0 %

#### Additional information

#### TSCA (Toxic Substances Control Act) - USA, United States of America

All chemical substances in this mixture are included on or are exempted from listing on the TSCA Inventory for Chemical Substances.

### California Proposition 65 - State of California

Based on available information this product does not contain any components or chemicals currently known to the State of California to cause cancer, birth defects or reproductive harm at levels which would be subject to Proposition 65.

### 15.2 Chemical safety assessment

No information available.



Trade name :	F.EE Haftschmierstoff für offene Antriebe - ArtNr. 1788818		
Revision date :	23.11.2023	Version (Revision) :	3.2.0 (3.1.0)
Print date :	07.12.2023		

### **SECTION 16: Other information**

### 16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP]  $\cdot$  13. Waste codes/waste designations according to EWC/AVV  $\cdot$  15. National regulations

16.2 Abbreviations and acronyms None
16.3 Key literature references and sources for data Includes supplements in accordance with Regulation (EU) 2020/878 of June 18, 2020
16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP] The statement is derived from the properties of the single components.
16.5 Relevant H- and EUH-phrases (Number and full text) H302 Harmful if swallowed.
16.6 Training advice None
16.7 Additional information None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.