



TURMOPAST TAS C

M F HC 0 U -40



Date of issue: 25.11.2020

TURMOPAST TAS C is an anti-seize product with a temperature range up to 1100°C. At 200°C the pasty lubrication passes to a dry lubrication.

Special properties

- Very good wear protection
- Excellent corrosion protection
- Good adhesive properties
- Excellent high load carrying capacity
- Low coefficient of friction

Product Characteristics	Value	Dimension	Norm / Standard
Colour	grey / cupreous		
Density at 20°C	1,17	g/cm ³	DIN 51757
Operating temperature range	-40 to 1100	°C	
Thickener	Inorganic thickener		
Base oil	Synthetic hydrocarbons		
Unworked penetration	340 - 385	mm/10	DIN ISO 2137
Dropping point	none	°C	DIN ISO 2176

Application

TURMOPAST TAS C is used against the seizing of bolts, hinges and bolt connections, as well as for the lubrication of slow running bearings, excenters, cam disks, spindles and chains.

TURMOPAST TAS C is applied in firing and annealing plants, steam boilers, hot gas turbines, exhaust gas and drying plants, screw fittings of extruder heads, return pulleys in electrode kilns, conveyor plants, conveyor chains, kiln cars, chains and adjusting spindles of soot blowers.

Note

For a first application the application point should be dry and free of grease. For the application in rolling bearings, i.e. chamber dryers max. 1/10 of the cavity between inner and outer ring should be filled and equally spreaded.

Packaging units

25 x 100 g tubes, 6 x 1 kg cans, 5 kg bucket, 25 kg hobbock



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>