



NY O 9400/220

Multifunctional slideway oil "ISO VG 220"

NY O 9400/220 is a high-quality, multifunctional slideway oil containing a low-aromatic, paraffinic mineral oil and special ingredients to reduce friction, with anti-wear, anti-corrosive and load-bearing properties.

Product properties / advantages:

- specially developed slideway oil
- meets the requirements of combined hydraulic and slideway systems
- high lubricity
- good demulsification properties of water-miscible cooling lubricants
- excellent stability against ageing and oxidation
- protects against corrosive effects on ferrous and non-ferrous metals
- specially chosen additives improve wear protection

Technical data:

Appearance of concentrate	Density at 15 °C [kg/m³]	Kin. viscosity at 40 °C [mm²/s]	Flash point COC [°C]	Copper corrosion (3 h / 100 °C)
brown, clear	895	220	235	1b (slight tarnish)

Application:

Excellent friction-sliding behavior under severe operating conditions even at low flow rates.
Suitable for combined systems that operate hydraulics, gearbox and slide lubrication in horizontal and vertical directions.

Shelf life / Storage conditions:

stable for 24 months when stored at a temperature of 5 °C to 40 °C in unopened containers

Remarks:

Minor variations in colour, odour and appearance are possible due to the raw materials chosen. However, these have no influence on the functionality of the product.

All information on safe and proper handling can be found on the SDS.

For further product information please contact our sales representative or technical support.