

Technical Data Sheet

LITEA EP 00

Semi fluid EP grease

Description

LITEA EP 00 is semi fluid stringy grease for reduction units based on mineral oil and lithium soap characterized by strong mechanical resistance.

Use / Application

LITEA EP 00 is formulated for gear-cases, bevel wheels, worm gears, industrial gears and similar applications lubrication even if operating on medium-high working temperatures.

LITEA EP 00 is particularly suitable for use in central lubricating systems, for slideways lubrication, for bearings lubrication on industrial devices, tools, presses and other applications where NLGI 00 lubricant grease is requested.

Properties

- excellent adhesiveness
- oxidation resistance
- extreme pressure resistance
- water resistance
- outstanding protection against corrosion

Technical Data

Service temperature		°C	- 30 / + 120
Drop point	DIN ISO 2176	°C	ca. 175
Penetration	DIN ISO 2137	1/10 mm	400 - 430
Water resistance	DIN 51807 T1		1 - 90
Anti corrosive resistance	DIN 51802	degree	0
Thickener soap			Li 12-hydrostear.
Base oil viscosity at 40°C	DIN 51562	mm²/s	ca. 200
Timken Test	DIN 51434 T3	N	178
Designation	DIN 51502		GP 00 K-30
	ISO 6743-9		ISO-L-XBCEB 00

For more information please contact our application engineers

Ed. 07/17

Headquarters

NILS S.p.A – AG I-39014 Postal - I

I-39014 Postal - Burgstall (BZ) Via Stazione, 30 - Bahnhofstraße 30 Tel. +39 0473 29 24 00 Fax +39 0473 29 12 44 Sales department and warehouse

I-37019 Peschiera del Garda (VR) Via 11 Settembre, 22 Tel. +39 045 64 00 801 Fax +39 045 64 01 036 Sales department

I-30020 Noventa di Piave (VE) Via Roma, 125 Tel. +39 0421 30 74 82 Fax +39 0421 30 81 05





