

## 1. Product Description (Benefits)

- ✓ Maximum protection from rust and corrosion
- ✓ Good anti-wear and high speed and load carrying capacity (Mo type)
- ✓ Quality proved item, which has used over 10 years in leading automatic lubricator maker
- ✓ Wide service temperature (-30 °C ~ 130 °C)
- ✓ Mineral oil + Lithium complex, Yellowish brown

## 2. Application Part

- ✓ Constant velocity joints for automobiles
- ✓ Automatic grease lubricator
- ✓ Anti-wear, Anti-rust, high speed and load-carrying capacity

## 3. Product Data

Test item	Test method	Result
<b>Copper Corrosion</b> <b>grade</b>	ASTM D 4048	1A
<b>Worked Penetration</b> <b>0.1mm</b>	ASTM D 217	305 ~ 310
<b>Dropping Point</b> °C	ASTM D 566	190
<b>Oil Separation</b> wt%	KS M 2050	2.0
<b>Evaporation Loss</b> wt%	ASTM D 972	0.4
<b>Worked Stability</b> 0.1mm	KS M 217	350
<b>Extreme-Pressure Properties</b> N	ASTM D 2596	400

Note : The above data constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field test with the product selected for a specific application

## 4. Suggestion of Using

- ✓ Grease gun, various spreading apparatus, brush and automatic lubricating system

※ Storage : Approx. 12 months if the product is stored in the original closed container in a dry place