

1. Product Description (Benefits)

- ✓ Product designed specifically for the lubrication of food processing machinery
- ✓ Good grease lubricates capable of providing excellent lubrication in all of these environment : Covering the extremes of temperatures from oven to freezer operations, as well as high level of contamination from water, steam and cleaning agents
- ✓ Registered : HSF H1, DIN 51825 KPF2K-20, Kosher/Parve, Halal
- ✓ Wide service temperature (- 25 °C ~ 170 °C)
- ✓ Mineral oil + Aluminum complex, White

2. Application Part

- ✓ General rotating equipment lubrication, Conveyor bearings
- ✓ Automatic grease lubricator
- ✓ Anti-friction roller bearings under heavy or shock loading, Linkages and slides, Joints

3. Product Data

Test item	Test method	Result
Copper Corrosion grade	DIN 51811	1B
Worked Penetration 0.1mm	ASTM D 217	280
Dropping Point °C	ASTM D 2265	260
Viscosity of oil cSt(40°C)	ASTM D 445	220
4-Ball Wear Test mm	ASTM D 2266	0.5
Copper Strip Corrosion Rating	ASTM D 1743	Pass

Note : The above data constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field test with the product selected for a specific application

4. Suggestion of Using

- ✓ Grease gun, various spreading apparatus, brush and automatic lubricating system

※ Storage : Approx. 12 months if the product is stored in the original closed container in a dry place