

## 1. Product Description (Benefits)

- ✓ Excellent pump ability in central lubrication systems
- ✓ Good resistance to ambient media, water and water steam
- ✓ Good anti-wear and load carrying capacity, corrosion protection
- ✓ Good sealing effect, good adhesion
- ✓ Wide service temperature (-15 °C ~ 160 °C)
- ✓ Mineral oil + Urea, Beige

## 2. Application Part

- ✓ Drive rollers, Conveyor rollers
- ✓ Automatic grease lubricator
- ✓ Heating furnaces, drying stove
- ✓ Opening gate of bulk material equipment, Cooling bed conveyor system

## 3. Product Data

| Test item                                  | Test method | Result |
|--------------------------------------------|-------------|--------|
| <b>Copper Corrosion</b> <b>grade</b>       | ASTM D 4048 | 1A     |
| <b>Worked Penetration</b> <b>0.1mm</b>     | ASTM D 217  | 320    |
| <b>Dropping Point</b> °C                   | ASTM D 566  | > 260  |
| <b>Oil Separation</b> wt%                  | KS M 2050   | 1.2    |
| <b>Water washout characteristic</b><br>wt% | ASTM D 1264 | 1      |
| <b>Evaporation Loss</b> wt%                | ASTM D 972  | 0.12   |
| <b>Extreme-Pressure Properties</b><br>N    | ASTM D 2596 | > 250  |

Note : The above data constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field test with the product selected for a specific application

## 4. Suggestion of Using

- ✓ General automatic lubricating system and lubrication supply system

※ Storage : Approx. 12 months if the product is stored in the original closed container in a dry place