

FLUID-setral-STG 220 FD	Nr.060672
Fully synthetic H1 high-temperature chain oil of the latest generation	Packaging: 20ltr. can 200ltr. drum 15x 400ml can other packaging on request

Application

Chain lubrication of transport-, drive- and cam shaft chains up to +260°C in the food and pharmaceutical industry.

Properties

- H1 registered
- Kosher certified
- Halal certified
- Extremely low evaporation losses
- Excellent penetration properties
- Excellent wear protection
- Extremely low coefficient of friction
- Very good anti-corrosion properties
- Adhesive additives prevent dripping and spinning-off
- Chemical stable and ageing resistant, even in aggressive air
- High hydrolytic stability
- Silicone-free

Instructions

- Apply product according to the viscosity by spraying, dripping or brushing. Suitable also for central lubrication systems.
- The minimum shelf life in original sealed containers, stored in a cool and dry place (no direct sunlight) is about 3 years.
- Due to the variety of applications we highly recommend to always carry out corresponding tests prior to general use.

Setral Chemie GmbH
 Salzsteinstrasse 4
 D-82402 Seeshaupt
 Telefon: +49 (0) 88 01 97 10
 Telefax: +49 (0) 88 01 97 30
 Email: info@setral.net

Sétral S.à.r.l.
 13, rue Tannmuhle
 F-67310 Romanswiller
 Téléphone: +33 (0) 3 88 59 11 59
 Télécopie: +33 (0) 3 88 59 11 57
 Email: france@setral.net

All the information stated is intended to guide product selection and reflects the state of our knowledge at the time of publication. The above information is neither an assurance of warranted product properties nor a guarantee for usability for individual applications. All the information in this document may be changed without prior notice at any time. This version replaces all previous versions.

Technical data

NSF Registration-No.	144573		-
Colour	gelb/orange		DIN ISO 2049
Basis	Ester		-
Density, 20°C	0.94	g/cm ³	in house
Viscosity, kinematic at 40°C	220	mm ² /s	DIN 51562
Viscosity, kinematic at 100°C	19	mm ² /s	DIN 51562
Viscosity index	95		DIN ISO 2909
Flash point, COC	>260	°C	DIN EN ISO2592
Pour Point	<-25	°C	DIN 51583
Copper corrosion (24h/100°C)	1	rating	DIN ISO 2160
Temperature range	-20 - +260	°C	-

Setral Chemie GmbH
Salzsteinstrasse 4
D-82402 Seeshaupt
Telefon: +49 (0) 88 01 97 10
Telefax: +49 (0) 88 01 97 30
Email: info@setral.net

Sétral S.à.r.l.
13, rue Tannmuhle
F-67310 Romanswiller
Téléphone: +33 (0) 3 88 59 11 59
Télécopie: +33 (0) 3 88 59 11 57
Email: france@setral.net

All the information stated is intended to guide product selection and reflects the state of our knowledge at the time of publication. The above information is neither an assurance of warranted product properties nor a guarantee for usability for individual applications. All the information in this document may be changed without prior notice at any time. This version replaces all previous versions.