According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Shell Gadus 1963 Product code : 001M1740

Unique Formula Identifier : K3K2-J

(UFI)

: K3K2-J0NV-M00K-739R

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Automotive and industrial grease.

stance/Mixture

Uses advised against

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup-

plier

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Deutschland GmbH

Suhrenkamp 71-77 D-22335 Hamburg (+49) 40 6324-6255

Telephone : (+49) 40 6324-6255 Telefax : (+49) 40 6321-051

Contact for Safety Data : If you have any enquiries about the content of this SDS

Sheet please email lubricantSDS@shell.com

1.4 Emergency telephone number

: (+49) 30 3068 6700 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Hazard pictograms :



Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard according to CLP

criteria.

HEALTH HAZARDS:

H319 Causes serious eye irritation. ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to

CLP criteria.

Precautionary statements : Prevention:

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Sensitising components : Contains triazole derivatives.

May produce an allergic reaction.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used grease may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : A lubricating grease containing polyolefins and additives.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

SDS Number: Date of last issue: -Version Revision Date: 800010057295 1.0 09.09.2022 Print Date 02.01.2023

Components

Components	T =	Ta	
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Alkylated phenol ester	125643-61-0	Aquatic Chronic 4;	1 - 3
	406-040-9	H413	
	607-530-00-7		
Trimethyldihydroquinoline, homo-	26780-96-1	Aquatic Chronic 3;	1 - 3
polymer	500-051-3	H412	
Lithium complex thickener	12006-96-1	Acute Tox. 4; H302	1 - 2,9
'		Eye Dam. 1; H318	,
	01-2120772309-47	Repr. 2; H361d	
		specific concentration	
		limit	
		Repr. 2; H361d	
		>= 7,6 %	
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Triazole derivative	91273-04-0	Skin Corr. 1B; H314	0,01 - 0,09
	401-280-0	Skin Sens. 1A; H317	-,,-
	613-072-00-9	Aquatic Chronic 1;	
	01-0000015116-78	H410	
	01 0000013110-70	טו דוון	l

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait

for symptoms to develop.

Obtain medical attention even in the absence of apparent

wounds.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

VersionRevision Date:SDS Number:Date of last issue: -1.009.09.2022800010057295Print Date 02.01.2023

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

Local necrosis is evidenced by delayed onset of pain and

tissue damage a few hours following injection.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Notes to doctor/physician:

Treat symptomatically.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue dam-

age and loss of function.

Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthet-

ics, and wide exploration is essential.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon diox-

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke).

Carbon monoxide may be evolved if incomplete combustion

occurs.

Unidentified organic and inorganic compounds.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

Avoid contact with skin and eyes. 6.1.2 For emergency responders: Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions : Use appropriate containment to avoid environmental contami-

nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Shovel into a suitable clearly marked container for disposal or

reclamation in accordance with local regulations.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

7.2 Conditions for safe storage, including any incompatibilities

Storage class (TRGS 510) : 10, Combustible liquids

Further information on stor-

age stability

Keep container tightly closed and in a cool, well-ventilated

place

Use properly labeled and closable containers.

Store at ambient temperature.

Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high tem-

peratures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) : Not applicable

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Biological occupational exposure limits

No biological limit allocated.

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Eye washes and showers for emergency use.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear goggles for use against liquids and gas, combined with

face shield.

Approved to EU Standard EN166.

Wear full face shield if splashes are likely to occur.

If a local risk assessment deems it so then chemical splash goggles may not be required and safety glasses may provide

gloves approved to relevant standards (e.g. Europe: EN374,

adequate eye protection.

Hand protection

Remarks : Where hand contact with the product may occur the use of

US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is

Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

dependent on the exact composition of the glove material.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: -1.0 09.09.2022 800010057295 Print Date 02.01.2023

Respiratory protection No respiratory protection is ordinarily required under normal

conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appro-

priate combination of mask and filter.

Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)]

meeting EN14387 and EN143.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Semi-solid at ambient temperature. Physical state

Colour light brown

Odour Slight hydrocarbon

Odour Threshold Data not available

>= 220 °C Drop point

Method: IP 396

Melting / freezing point Not applicable

Initial boiling point and boiling : Data not available

range

Flammability

Flammability (solid, gas) Not applicable

Flammability (liquids) Not classified as flammable but will burn.

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /

upper flammability limit

Typical 10 %(V)

Lower explosion limit / Lower flammability limit Typical 1 %(V)

Flash point Method: Unspecified

Not applicable

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Auto-ignition temperature : > 320 °C

Decomposition temperature

Decomposition tempera-

ture

Data not available

pH : Not applicable

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 90 - 110 mm2/s (40,0 °C)

Method: ASTM D445

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n- : log Pow: > 6

octanol/water (based on information on similar products)

Vapour pressure : < 0,5 Pa (20 °C)

estimated value(s)

Density : 1.000 kg/m3 (15,0 °C)

Method: Unspecified

Relative vapour density : > 1

estimated value(s)

9.2 Other information

Explosives : Classification Code: Not classified

Oxidizing properties : Data not available

Flammability (liquids) : Not classified as flammable but will burn.

Evaporation rate : Data not available

Conductivity : This material is not expected to be a static accumulator.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (rat): > 5.000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks : Slightly irritating to skin.

Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Serious eye damage/eye irritation

Product:

Remarks : Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Remarks : For respiratory and skin sensitisation:

Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic

Based on available data, the classification criteria are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Product:

Remarks : Not a carcinogen.

Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Alkylated phenol ester	No carcinogenicity classification.
Trimethyldihydroquinoline, homopolymer	No carcinogenicity classification.
Lithium complex thickener	No carcinogenicity classification.
Triazole derivative	No carcinogenicity classification.

Reproductive toxicity

Product:

Effects on fertility :

Remarks: Not a developmental toxicant., Does not impair

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

fertility., Based on available data, the classification criteria are

not met.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Components:

Lithium complex thickener:

Effects on foetal develop-

ment

Remarks: Based on available data, the classification criteria

are not met.

STOT - single exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Further information

Product:

Remarks : Used grease may contain harmful impurities that have accu-

mulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health

and the environment on disposal.

ALL used grease should be handled with caution and skin

contact avoided as far as possible.

Remarks : High pressure injection of product into the skin may lead to

local necrosis if the product is not surgically removed.

Remarks : Slightly irritating to respiratory system.

Remarks : Classifications by other authorities under varying regulatory

frameworks may exist.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic tox-

icity)

Remarks: Based on available data, the classification criteria are not

met

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: Based on available data, the classification criteria are not

met.

Toxicity to microorganisms

Remarks: Based on available data, the classification criteria are not

met.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.

Major constituents are inherently biodegradable, but contains com-

ponents that may persist in the environment.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

12.4 Mobility in soil

Product:

Mobility : Remarks: Semi-solid under most environmental conditions., If

it enters soil, it will adsorb to soil particles and will not be mo-

bile.

Remarks: Floats on water.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: -1.0 09.09.2022 800010057295 Print Date 02.01.2023

12.5 Results of PBT and vPvB assessment

Product:

This mixture does not contain any REACH registered sub-Assessment

stances that are assessed to be a PBT or a vPvB..

12.6 Endocrine disrupting properties

no data available

12.7 Other adverse effects

Product:

Additional ecological information

Does not have ozone depletion potential, photochemical ozone crea-

tion potential or global warming potential.

Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions

of use.

Poorly soluble mixture.

Causes physical fouling of aquatic organisms.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recover or recycle if possible. Product

> It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Waste, spills or used product is dangerous waste.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater

contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

SDS Number: Version **Revision Date:** Date of last issue: -1.0 09.09.2022 800010057295 Print Date 02.01.2023

national, and local laws and regulations.

Local legislation

Waste catalogue

EU Waste Disposal Code (EWC):

Waste Code

12 01 12*

Remarks Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Classification of waste is always the responsibility of the end

user.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good **ADR** Not regulated as a dangerous good **RID** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good **ADR** Not regulated as a dangerous good **RID** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good **ADR** Not regulated as a dangerous good RID Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.4 Packing group

ADN Not regulated as a dangerous good : NST 3411 lubricating greases

CDNI Inland Water Waste

Agreement

15/31

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

i Not regulated as a dangerous good

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Product is not subject to Authorisa-

(Annex XIV) tion under REACH.

Water hazard class (Germa: WGK 1 slightly hazardous to water

ny) Remarks: Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Technische Anleitung Luft: Product not listed by name. Observe section 5.2.5 in connection with section 5.4.9

Product is subject Betriebs-Sicherheits-Verordnung (BetrSichV).

Compliance with paragraph 22 of Youth Employment Law.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

The components of this product are reported in the following inventories:

REACH : All components listed or polymer exempt.

TSCA : All components listed.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H361d : Suspected of damaging the unborn child.

H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Repr. : Reproductive toxicity Skin Corr. : Skin corrosion

Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub-

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: - 1.0 09.09.2022 800010057295 Print Date 02.01.2023

stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for op-

erators.

Other information : No Exposure Scenario annex is attached to this safety data

sheet. It is a non-classified mixture containing hazardous substances as detailed in Section 3; relevant information from Exposure Scenarios for the hazardous substances contained have been integrated into the core sections 1-16 of this SDS.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Classification of the mixture:

Eye Irrit. 2 H319 Expert judgement and weight of evi-

dence determination.

Classification procedure:

Identified Uses according to the Use Descriptor System Uses - Worker

Title : General use of lubricants and greases in vehicles or machin-

ery.- Industrial

Uses - Worker

Title : General use of lubricants and greases in vehicles or machin-

ery.- Professional

Uses - Worker

Title : Use of lubricants and greases in open systems.- Industrial

Uses - Worker

Title : Use of lubricants and greases in open systems.- Professional

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Exposure Scenario - Worker

30000000170	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC8b, PROC9 Environmental Release Categories: ERC4, ERC7, ATIEL- ATC SPERC 4.Bi.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.

Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated
stance in Mixture/Article	differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)Use in closed process, no likelihood of expo-	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

sure	
Initial factory fill of equip-	No other specific measures identified.
mentUse in contained sys-	
temsUse in closed, contin-	
uous process with occa-	
sional controlled exposure-	
Transfer of substance or	
preparation into small con-	
tainers (dedicated filling	
line, including weighing)	
Initial factory fill of equip-	Provide a good standard of general or controlled ventilation (5
ment(open sys-	to 15 air changes per hour).
tems)Transfer of substance	Avoid carrying out activities involving exposure for more than
or preparation (charging/	4 hours
discharging) from/ to ves-	
sels/ large containers at	
dedicated facilities	
Operation of equipment	No other specific measures identified.
containing engine oils and	
similar.Use in contained	
systemsUse in closed pro-	
cess, no likelihood of expo-	
sure	
Equipment cleaning and	Drain down system prior to equipment opening or mainte-
maintenanceTransfer of	nance.
substance or preparation	Provide a good standard of general ventilation (not less than
(charging/ discharging)	3 to 5 air changes per hour).
from/ to vessels/ large containers at dedicated facili-	Wear chemically resistant gloves (tested to EN374) in combi-
ties	nation with specific activity training. Retain drain downs in sealed storage pending disposal or for
lies	subsequent recycle.
	Subsequent recycle.
Equipment cleaning and	Drain down system prior to equipment opening or mainte-
maintenanceOperation is	nance.
carried out at elevated tem-	Provide extract ventilation to emission points when contact
perature (> 20°C above	with warm (>50oC) product is likely.
ambient tempera-	Wear chemically resistant gloves (tested to EN374) in combi-
ture).Transfer of substance	nation with intensive management supervision controls.
or preparation (charging/	Retain drain downs in sealed storage pending disposal or for
discharging) from/ to ves-	subsequent recycle.
sels/ large containers at	' '
dedicated facilities	
Storage.Use in closed pro-	Store substance within a closed system.
cess, no likelihood of expo-	,
sureUse in closed, continu-	
ous process with occasion-	
al controlled exposure	

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
-----------	---------------------

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Section 3.1 - Health

The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Where other Risk Management Measures/Operational Conditions are adopted, then users	
should ensure that risks are managed to at least equivalent levels.	

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Exposure Scenario - Worker

Exposure Scenario - Worker		
3000000171		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	General use of lubricants and greases in vehicles or machin- ery Professional	
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC8a, PROC8b, PROC20 Environmental Release Categories: ERC9a, ERC9b, ATIEL-ATC SPERC 9.Bp.v1	
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.

Section 2.1	Control of Worker Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP		
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,		
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Operation of equipment containing engine oils and	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: -09.09.2022 800010057295 Print Date 02.01.2023 1.0

similar.Use in contained systemsUse in closed pro-	
cess, no likelihood of expo-	
sure	
Material transfersNon- dedicated facilityTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large con- tainers at non-dedicated facilities	Avoid carrying out activities involving exposure for more than 4 hours Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilitiesHeat and pressure transfer fluids in dispersive, professional use but closed systems	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	

The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Where other Risk Management Measures/Operational Conditions are adopted, then users		

snould ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Exposure Scenario - Worker

Exposure Scenario - Worke	Exposure Scenario - Worker	
30000000172		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Use of lubricants and greases in open systems Industrial	
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC7, PROC8b, PROC9, PROC10, PROC13 Environmental Release Categories: ERC4, ATIEL-ATC SPERC 4.Ci.v1	
Scope of process	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.

Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP	•
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated	
stance in Mixture/Article	differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Assumes a good basic standard of occupational hygiene is implemented.		

Contributing Scenarios	Risk Management Measures	
General measures applica-	Avoid direct skin contact with product. Identify potential areas	
ble to all activities.	for indirect skin contact. Wear gloves (tested to EN374) if	
	hand contact with substance likely. Clean up contamina-	
	tion/spills as soon as they occur. Wash off any skin contami-	
	nation immediately. Provide basic employee training to pre-	
	vent / minimise exposures and to report any skin problems	
	that may develop.	
	Other skin protection measures such as impervious suits and	
	face shields may be required during high dispersion activities	
	which are likely to lead to substantial aerosol release, e.g.	
	spraying.	
	Use suitable eye protection.	

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

	Avoid direct eye contact with product, also via contamination on hands.
Material transfersManual- Transfer of substance or preparation (charging/ dis- charging) from/ to vessels/ large containers at dedicat- ed facilities	Avoid carrying out activities involving exposure for more than 1 hour.
Material transfersAutomated process with (semi) closed systems.Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilitiesTransfer of substance or preparation into small containers (dedicated filling line, including weighing)	Ensure material transfers are under containment or extract ventilation.
Roller, spreader, flow applicationRoller application or brushing	Provide extraction ventilation at points where emissions occur.
SprayingIndustrial spraying	Carry out in a vented booth or extracted enclosure. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Treatment by dipping and pouringTreatment of articles by dipping and pouring	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	Drain down system prior to equipment opening or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Exposure Scenario - Worker

Exposure Scenario - Worker	
30000000173	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use of lubricants and greases in open systems Professional
Use Descriptor	Sector of Use: SU22
	Process Categories: PROC1, PROC2, PROC8a, PROC10,
	PROC11, PROC13
	Environmental Release Categories: ERC8a, ERC8d,
	ATIEL-ATC SPERC 8.Cp.v1
Scope of process	Covers use of lubricants and greases in open systems, in-
	cluding application of lubricant to work pieces or equipment
	by dipping, brushing or spraying (without exposure to heat),
	e.g. mould releases, corrosion protection, slideways. Includes
	associated product storage, material transfers, sampling and
	maintenance activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.

Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STF	•
Concentration of the Sub-	Covers use of substance/product up to 1	00% (unless stated
stance in Mixture/Article	differently).,	
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		
Assumes use at not more than 20°C above ambient temperature (unless stated differently).		
Assumes a good basic stand	dard of occupational hygiene is implemente	d.

Contributing Scenarios	Risk Management Measures
General measures applica-	Avoid direct skin contact with product. Identify potential areas
ble to all activities.	for indirect skin contact. Wear gloves (tested to EN374) if
	hand contact with substance likely. Clean up contamina-
	tion/spills as soon as they occur. Wash off any skin contami-
	nation immediately. Provide basic employee training to pre-
	vent / minimise exposures and to report any skin problems
	that may develop.
	Other skin protection measures such as impervious suits and
	face shields may be required during high dispersion activities
	which are likely to lead to substantial aerosol release, e.g.
	spraying.
	Use suitable eye protection.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

	Avoid direct eye contact with product, also via contamination on hands.
Material transfersManual- Transfer of substance or preparation (charging/ dis- charging) from/ to vessels/ large containers at non- dedicated facilities	Avoid carrying out activities involving exposure for more than 1 hour.
Roller, spreader, flow applicationRoller application or brushing	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
SprayingNon industrial spraying	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 1 hour. Wear a respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable coveralls to prevent exposure to the skin. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Treatment by dipping and pouringTreatment of articles by dipping and pouring	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	Drain down system prior to equipment opening or maintenance. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.

Section 2.2	Control of Environmental Exposure	
No exposure assessment pre	sented for the environment.	

EXI COOKE ESTIMATION	SECTION 3	EXPOSURE ESTIMATION
----------------------	-----------	---------------------

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus 1963

Version Revision Date: SDS Number: Date of last issue: 1.0 09.09.2022 800010057295 Print Date 02.01.2023

Section 3.1 - Health

The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.		

Section 4.2 - Environment

No exposure assessment presented for the environment.