



Technical Data Sheet

- Long Life
- Improved Efficiency
- Lithium Complex

Shell Gadus S5 V100CSK

Advanced Multipurpose Grease

Shell Gadus S5 V100CSK is a lithium complex grease based on synthetic base oils, containing antioxidants, wear- and rust preventing additives

The product contains a special friction modifier which is suitable for high speed bearings, taper roller bearings and cylindrical bearings, type NJ, NUP plus applications with an angle ring.

DESIGNED TO MEET CHALLENGES

Main Applications



Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties	Method	Shell Gadus S5 V100CSK
NLGI Consistency		2
Colour		Light Brown
Dropping Point	°C minimum	220
Base Oil Viscosity	@40°C cSt	100
Base Oil Viscosity	@100°C cSt	14
Rust Preventing Properties : SKF Emcor distilled water		0/0

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health, Safety & Environment

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

Protect the Environment Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell Representative.