According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

 Version
 Revision Date:
 SDS Number:
 Date of last issue:

 1.0
 06.09.2024
 800010065264
 Print Date 07.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Shell Tactic EMV Gadus S3 V460DM 2

Product code : 007A3864

Unique Formula Identifier : YWJ4-Y0MQ-400V-GVV6

(UFI)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Automotive and industrial grease.

stance/Mixture

Uses advised against

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup-

plier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Deutschland GmbH

Suhrenkamp 71-77 22335 Hamburg

Germany

Telephone : (+49) 40 6324-6255 Telefax : (+49) 40 6321-051

Contact for Safety Data : If you have any enquiries about the content of this SDS

Sheet please email lubricantSDS@shell.com

1.4 Emergency telephone number

: (+49) 30 3068 6700 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

Hazard pictograms :



Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard according to CLP

criteria.

HEALTH HAZARDS:

H319 Causes serious eye irritation. ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to

CLP criteria.

Precautionary statements : Prevention:

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Sensitising components : Contains Zinc Naphthenate

May produce an allergic reaction.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used grease may contain harmful impurities.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : A lubricating grease containing highly-refined mineral oils and

additives.

The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

Classification based on DMSO extract content < 3% (Regula-

tion (EC) 1272/2008, Annex VI, Part 3, Note L).

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Reaction products of boric acid and lithium hydroxide	Not Assigned 701-475-3 01-2120772309-47	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d specific concentration limit Repr. 2; H361d 7,8 %	1 - 2,9
Zinc naphthenate	84418-50-8 282-762-6 01-2119988500-34	Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	1 - 1,49
Alkaryl amine	68411-46-1 270-128-1 01-2119491299-23	Repr. 2; H361f	0,1 - 0,9

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait

for symptoms to develop.

Obtain medical attention even in the absence of apparent

wounds.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses, if present and easy to do. Continue

rinsing

Transport to the nearest medical facility for additional treat-

ment.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Oil acne/folliculitis signs and symptoms may include formation

of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. Not considered to be an inhalation hazard under normal con-

ditions of use.

Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, cough-

ing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, or swelling.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Local necrosis is evidenced by delayed onset of pain and

tissue damage a few hours following injection.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Treat symptomatically.
Notes to doctor/physician:
Treat symptomatically.

Call a doctor or poison control center for guidance.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue dam-

age and loss of function.

Because entry wounds are small and do not reflect the seri-

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

 Version
 Revision Date:
 SDS Number:
 Date of last issue:

 1.0
 06.09.2024
 800010065264
 Print Date 07.09.2024

ousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon diox-

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke).

Carbon monoxide may be evolved if incomplete combustion

occurs.

Unidentified organic and inorganic compounds.

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

Avoid contact with skin and eyes. 6.1.2 For emergency responders: Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions : Use appropriate containment to prevent uncontrolled release.

Prevent from spreading or entering drains, ditches or rivers by

using sand, earth, or other appropriate barriers.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Shovel into a suitable clearly marked container for disposal or

reclamation in accordance with local regulations.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

7.2 Conditions for safe storage, including any incompatibilities

Storage class (TRGS 510) : 13, Non Combustible Solids

Further information on stor-

age stability

Keep container tightly closed and in a cool, well-ventilated

place.

Use properly labeled and closable containers.

Store at ambient temperature.

Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high tem-

peratures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) : Not applicable

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral	Not As- signed	TWA (inhalable fraction)	5 mg/m3	US. ACGIH Threshold Limit Values

Biological occupational exposure limits

No biological limit allocated.

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear full face shield if splashes are likely to occur.

Approved to EU Standard EN166.

Hand protection

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

 Version
 Revision Date:
 SDS Number:
 Date of last issue:

 1.0
 06.09.2024
 800010065264
 Print Date 07.09.2024

Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection

Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.
Protective clothing approved to EU Standard EN14605.

Respiratory protection

No respiratory protection is ordinarily required under normal conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

Check with respiratory protective equipment suppliers.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)]

meeting EN14387 and EN143.

Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Semi-solid at ambient temperature.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Date of last issue: -Version **Revision Date:** SDS Number: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

Colour black

Odour Slight hydrocarbon

Odour Threshold Data not available

Melting point/freezing point Method: Unspecified

Melting / freezing point Not applicable

>= 240 °C Drop point

Method: IP 396

pour point Not applicable

Initial boiling point and boiling

range

Data not available

Flammability

Flammability (solid, gas) Not applicable

Not classified as flammable but will burn. Flammability (liquids)

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /

upper flammability limit

Typical 10 %(V)

Lower explosion limit /

Lower flammability limit

Typical 1 %(V)

Flash point Not applicable

Auto-ignition temperature > 320 °C

Decomposition temperature

Decomposition tempera-

ture

Data not available

рΗ Not applicable

Viscosity

Viscosity, dynamic Data not available

Solubility(ies)

negligible Water solubility

Solubility in other solvents Data not available

Partition coefficient: nlog Pow: > 6

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

octanol/water (based on information on similar products)

Vapour pressure : < 0,5 Pa (20 °C)

estimated value(s)

Density : 1.000 kg/m3 (15,0 °C)

Method: Unspecified

Relative vapour density : > 1

estimated value(s)

Particle characteristics

Particle size : Data not available

9.2 Other information

Explosive properties : Classification Code: Not classified

Oxidizing properties : Data not available

Flammability (liquids) : Not classified as flammable but will burn.

Evaporation rate : Data not available

Conductivity : This material is not expected to be a static accumulator.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

 Version
 Revision Date:
 SDS Number:
 Date of last issue:

 1.0
 06.09.2024
 800010065264
 Print Date 07.09.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (rat): > 5.000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks : Slightly irritating to skin.

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks : Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Remarks : For respiratory and skin sensitisation:

Not a sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic

Based on available data, the classification criteria are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

Carcinogenicity

Product:

Remarks : Not a carcinogen.

Based on available data, the classification criteria are not met.

Remarks : Product contains mineral oils of types shown to be non-

carcinogenic in animal skin-painting studies.

Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are

not met.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Used grease may contain harmful impurities that have accu-

mulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health

and the environment on disposal.

ALL used grease should be handled with caution and skin

contact avoided as far as possible.

Remarks : High pressure injection of product into the skin may lead to

local necrosis if the product is not surgically removed.

Remarks : Slightly irritating to respiratory system.

Remarks : Classifications by other authorities under varying regulatory

frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic tox- : Remarks: Based on available data, the classification criteria are not

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

 Version
 Revision Date:
 SDS Number:
 Date of last issue:

 1.0
 06.09.2024
 800010065264
 Print Date 07.09.2024

icity) met.

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: Based on available data, the classification criteria are not

met.

Toxicity to microorganisms

Remarks: Based on available data, the classification criteria are not

met.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.

Major constituents are inherently biodegradable, but contains com-

ponents that may persist in the environment.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

12.4 Mobility in soil

Product:

Mobility : Remarks: Semi-solid under most environmental conditions., If

it enters soil, it will adsorb to soil particles and will not be mo-

bile.

Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture does not contain any REACH registered sub-

stances that are assessed to be a PBT or a vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor: Does not have ozone depletion potential, photochemical ozone crea-

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

mation tion potential or global warming potential.

Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions

of use.

Poorly soluble mixture.

Causes physical fouling of aquatic organisms.

Mineral oil does not cause chronic toxicity to aquatic organisms at

concentrations less than 1 mg/l.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater

contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably

to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local legislation

Waste catalogue

EU Waste Disposal Code (EWC):

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

Waste Code

12 01 12*

Remarks : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Classification of waste is always the responsibility of the end

user.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good
: Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

I Not regulated as a dangerous good

I Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good CDNI Inland Water Waste : NST 3411 lubricating greases

Agreement

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADN : Not regulated as a dangerous good

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

: Product is not subject to Authorisa-

tion under REACH.

Water hazard class (Germa- : WGK 1 slightly hazardous to water

ny)

Remarks: Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Technische Anleitung Luft: Product not listed by name. Observe section 5.2.5 in connection with section 5.4.9

Product is subject to Betriebs-Sicherheits-Verordnung (BetrSichV).

Compliance with paragraph 22 of Youth Employment Law.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

The components of this product are reported in the following inventories:

REACH : Not established.

TSCA : All components listed.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: - 1.0 06.09.2024 800010065264 Print Date 07.09.2024

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H361d : Suspected of damaging the unborn child.

H361f : Suspected of damaging fertility. (Causing atrophy of the tes-

tes)

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet;

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: -1.0 06.09.2024 800010065264 Print Date 07.09.2024

SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice Provide adequate information, instruction and training for op-

Other information A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

Classification of the mixture:

Classification procedure:

Eye Irrit. 2 H319 Expert judgement and weight of evi-

dence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title General use of lubricants and greases in vehicles or machin-

> ery. - Industrial

Uses - Worker

General use of lubricants and greases in vehicles or machin-Title

ery.

- Professional

Uses - Worker

Title Use of lubricants and greases in open systems.

- Industrial

Uses - Worker

Title Use of lubricants and greases in open systems.

- Professional

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

DE / EN

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: -1.0 06.09.2024 800010065264 Print Date 07.09.2024

Exposure Scenario - Worker

Exposure coeriano Work	
30000000170	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machin-
	ery Industrial
Use Descriptor	Sector of Use: SU3
	Process Categories: PROC1, PROC2, PROC8b, PROC9
	Environmental Release Categories: ERC4, ERC7, ATIEL-
	ATC SPERC 4.Bi.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of
	containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for the environment.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).	
Frequency and Duration of	f Use	
Covers daily exposures up to	o 8 hours (unless stated differently).	
Other Operational Condition	ons affecting Exposure	
	an 20°C above ambient temperature (unless stated differently).	

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)Use in closed process, no likelihood of exposure	No other specific measures identified.
Initial factory fill of equip-	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

mentUse in contained sys-		
temsUse in closed, contin-		
uous process with occa-		
sional controlled exposure-		
Transfer of substance or		
preparation into small con-		
tainers (dedicated filling		
line, including weighing)		
Initial factory fill of equip-	Provide a good standard of general or co	ntrolled ventilation (5
ment(open sys-	to 15 air changes per hour).	interior vermidation (e
tems)Transfer of substance	Avoid carrying out activities involving exp	osure for more than
or preparation (charging/	4 hours	
discharging) from/ to ves-	Tilodio	
sels/ large containers at		
dedicated facilities		
Operation of equipment	No other specific measures identified.	
containing engine oils and	ino other specific measures identified.	
similar.Use in contained		
systemsUse in closed pro-		
cess, no likelihood of expo-		
sure		
	Drain days a stam prior to aguinment on	aning or mainta
Equipment cleaning and maintenanceTransfer of	Drain down system prior to equipment op	ening or mainte-
	nance.	lation (not loss than
substance or preparation	Provide a good standard of general ventil 3 to 5 air changes per hour).	iation (not less than
(charging/ discharging) from/ to vessels/ large con-	Wear chemically resistant gloves (tested	to EN274) in combi
tainers at dedicated facili-	nation with specific activity training.	to ENST4) III Combi-
ties	Retain drain downs in sealed storage per	nding disposal or for
ues	subsequent recycle.	iding disposal of for
	subsequent recycle.	
Equipment cleaning and	Drain down system prior to equipment op	ening or mainte-
maintenanceOperation is	nance.	ening of mainte-
carried out at elevated tem-	Provide extract ventilation to emission po	inte when contact
perature (> 20°C above	with warm (>50oC) product is likely.	into when contact
ambient tempera-	Wear chemically resistant gloves (tested	to EN274) in combi
ture). Transfer of substance	nation with intensive management superv	
or preparation (charging/	Retain drain downs in sealed storage per	
discharging) from/ to ves-		iding disposal of 101
sels/ large containers at	subsequent recycle.	
dedicated facilities		
Storage.Use in closed pro-	Store substance within a closed system.	
cess, no likelihood of expo-	Store substance within a closed system.	
sureUse in closed, continu-		
ous process with occasion-		
al controlled exposure	Central of Environmental Function	
Section 2.2	Control of Environmental Exposure	
No exposure assessment pre	sentea for the environment.	

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The Risk Management Measures/Operational Conditions that are identified in the Exposure		
Scenario are the outcome of a quantitative and qualitative assessment that covers this		

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

product.

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO	
Section 4.1 - Health		
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.		

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

Exposure Scenario - Worker

30000000171	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machin- ery Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC8a, PROC8b, PROC20 Environmental Release Categories: ERC9a, ERC9b, ATIEL-ATC SPERC 9.Bp.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
No exposure assessment presented for the environment.		
Control of Worker Exposure		
Product Characteristics		
Liquid, vapour pressure < 0.5 kPa at STP		
Covers use of substance/product up to 100% (unless stated differently).,		
Frequency and Duration of Use		
Covers daily exposures up to 8 hours (unless stated differently).		
Other Operational Conditions affecting Exposure		

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Operation of equipment containing engine oils and similar. Use in contained systems Use in closed pro-	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

cess, no likelihood of expo-		
sure		
Material transfersNon-	Avoid carrying out activities involving exp	osure for more than
dedicated facilityTransfer of	4 hours	
substance or preparation	Wear chemically resistant gloves (tested	to EN374) in combi-
(charging/ discharging)	nation with specific activity training.	
from/ to vessels/ large con-		
tainers at non-dedicated		
facilities		
Equipment cleaning and	Drain down system prior to equipment op	ening or mainte-
maintenanceTransfer of	nance.	
substance or preparation	Retain drain downs in sealed storage per	nding disposal or for
(charging/ discharging)	subsequent recycle.	
from/ to vessels/ large con-		
tainers at dedicated facili-		
tiesHeat and pressure		
transfer fluids in dispersive,		
professional use but closed		
systems		
Storage.Use in closed pro-	Store substance within a closed system.	
cess, no likelihood of expo-		
sureUse in closed, continu-		
ous process with occasion-		
al controlled exposure		
Section 2.2	Control of Environmental Exposure	<u> </u>
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	

The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: -1.0 06.09.2024 800010065264 Print Date 07.09.2024

Exposure Scenario - Worker

	20000000470	
30000000172		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Use of lubricants and greases in open systems Industrial	
Use Descriptor	Sector of Use: SU3	
Coo Dood.ip.o.	Process Categories: PROC1, PROC2, PROC7, PROC8b, PROC9, PROC10, PROC13	
	Environmental Release Categories: ERC4, ATIEL-ATC SPERC 4.Ci.v1	
Scope of process	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Condition	ons affecting Exposure
Assumes use at not more than 20°C above ambient temperature (unless stated differently).	
Assumes a good basis standard of assumptional hygiens is implemented	

Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures applica-	Avoid direct skin contact with product. Identify potential areas
ble to all activities.	for indirect skin contact. Wear gloves (tested to EN374) if
	hand contact with substance likely. Clean up contamina-
	tion/spills as soon as they occur. Wash off any skin contami-
	nation immediately. Provide basic employee training to pre-
	vent / minimise exposures and to report any skin problems
	that may develop.
	Other skin protection measures such as impervious suits and
	face shields may be required during high dispersion activities
	which are likely to lead to substantial aerosol release, e.g.
	spraying.
	Use suitable eye protection.
	Avoid direct eye contact with product, also via contamination
	on hands.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

Material transfersManual- Transfer of substance or preparation (charging/ dis- charging) from/ to vessels/ large containers at dedicat- ed facilities Material transfersAutomat-	Avoid carrying out activities involving exposure for more than 1 hour. Ensure material transfers are under containment or extract
ed process with (semi) closed systems. Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	ventilation.
Roller, spreader, flow applicationRoller application or brushing	Provide extraction ventilation at points where emissions occur.
SprayingIndustrial spraying	Carry out in a vented booth or extracted enclosure. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Treatment by dipping and pouringTreatment of articles by dipping and pouring	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	Drain down system prior to equipment opening or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment pre	sented for the environment.

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The Risk Management Measures/Operational Conditions that are identified in the Exposure	

The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

Exposure Scenario - Worker

	Exposure Scenario - Worker	
30000000173		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Use of lubricants and greases in open systems Professional	
Use Descriptor	Sector of Use: SU22	
	Process Categories: PROC1, PROC2, PROC8a, PROC10,	
	PROC11, PROC13	
	Environmental Release Categories: ERC8a, ERC8d,	
	ATIEL-ATC SPERC 8.Cp.v1	
Scope of process	Covers use of lubricants and greases in open systems, in-	
	cluding application of lubricant to work pieces or equipment	
	by dipping, brushing or spraying (without exposure to heat),	
	e.g. mould releases, corrosion protection, slideways. Includes	
	associated product storage, material transfers, sampling and	
	maintenance activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated
stance in Mixture/Article	differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	

Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.

Contributing Scenarios	Risk Management Measures
General measures applica-	Avoid direct skin contact with product. Identify potential areas
ble to all activities.	for indirect skin contact. Wear gloves (tested to EN374) if
	hand contact with substance likely. Clean up contamina-
	tion/spills as soon as they occur. Wash off any skin contami-
	nation immediately. Provide basic employee training to pre-
	vent / minimise exposures and to report any skin problems
	that may develop.
	Other skin protection measures such as impervious suits and
	face shields may be required during high dispersion activities
	which are likely to lead to substantial aerosol release, e.g.
	spraying.
	Use suitable eye protection.
	Avoid direct eye contact with product, also via contamination
	on hands.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

Material transfersManual- Transfer of substance or preparation (charging/ dis- charging) from/ to vessels/ large containers at non- dedicated facilities	Avoid carrying out activities involving exposure for more than 1 hour.
Roller, spreader, flow applicationRoller application or brushing	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
SprayingNon industrial spraying	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 1 hour. Wear a respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable coveralls to prevent exposure to the skin. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Treatment by dipping and pouringTreatment of articles by dipping and pouring	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	Drain down system prior to equipment opening or maintenance. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment pre	esented for the environment.

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
The Risk Management Measures/Operational Conditions that are identified in the Exposure		
Scenario are the outcome of a quantitative and qualitative assessment that covers this		

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Tactic EMV Gadus S3 V460DM 2

Version Revision Date: SDS Number: Date of last issue: 1.0 06.09.2024 800010065264 Print Date 07.09.2024

product.

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment

No exposure assessment presented for the environment.