Safety Data Sheet



Issue Date 18-Jun-2013 Revision date 03-Mar-2015 Version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code 654

Product name GREASEWAY HT 2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Lubricant.

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Company Name Supplier

Statoil Fuel & Retail Lubricants Sweden AB, Statoil Fuel & Retail Lubricants Sweden AB,

Box 194, 149 22 Nynäshamn, Box 194, 149 22 Nynäshamn,

Sweden, Sweden

+46 8 429 60 00 +46 8 429 60 00

For further information, please contact

Contact Point HSE Advisor

Email address BASP MD RD HSEA@statoilfuelretail.com

Company Phone Number +46 8 429 60 00

1.4. Emergency telephone number

Emergency telephone - §45 - (EC)1272/2008					
Europe	112				
Czech Republic	+420 224 91 92 93/+420 224 91 54 02 (Poison Information)				
Denmark	+45 82 12 12 12 (Poison Information)				
Finland	+358 09 471 977 (Poison Information)				
Latvia	+ 371 7042468 (Poison Information)				
Lithuania	+370 5 236 20 52 (Poison Information)				
Norway	+47 22 59 13 00 (Poison Information)				
Poland	+48 426 314 502 (Poison Information)				
Slovakia	+ 421 2 5465 2307 (Poison Information)				
Sweden	+46 8 33 70 43 (Emergency Responce Center)				
Estonia	+372 626 9390 (Poison Information)				

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [GHS]

Classification according to 67/548/EEC or 1999/45/EC

This product does not meet the classification requirements of the current legislation

GREASEWAY HT 2

Full text of R-phrases: see section 16

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [GHS]

EUH210 - Safety data sheet available on request

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1 Substances

Only hazardous substances above thresholds are shown below

Chemical name	EC No	CAS No	weight-%	Classification according to 67/548/EEC or 1999/45/EC	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH registration number
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	270-128-1	68411-46-1	1-5%	R52/53	STOT RE 2 (H373) Aquatic Chronic 3 (H412)	01-2119491299-23

Full text of R-phrases: see section 16

Full text of H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do

not get in eyes, on skin, or on clothing.

Eye Contact Wash with plenty of water. If eye irritation persists: get medical advice/attention.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. Wash

contaminated clothing before reuse.

Ingestion Clean mouth with water. Do NOT induce vomiting. Potential for aspiration if swallowed. Get

medical attention.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

Self-protection of the first aiderUse personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None under normal use conditions.

4.3. Indication of any immediate medical attention and special treatment needed

GREASEWAY HT 2

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use CO2, dry chemical, or foam.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Cool drums with water spray.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection recommended in Section 8.

Extremely slippery when spilled.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4. Reference to other sections

Other information

See Section 12: Ecological information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Extremely slippery when spilled.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Store in a dry place. Store in a closed container. Protect from moisture.

7.3. Specific end use(s)

Specific use(s)

Lubricant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Chemical name	Sweden	Denmark	Norway	Finland	Estonia
Oil mist/smoke	NGV 8 h: 1 mg/m³, KTV 15 min: 3 mg/m³	8h: 1 mg/m³	8h: 1 mg/m³	8h: 5 mg/m³	TWA 8h: 1 mg/m³
Chemical name	Latvia	Lithuania	Poland	Russia	Slovakia
Oil mist/smoke	8h: 5 mg/m³	IPRV 8h: 1 mg/m³, TPRV 15 min: 3 mg/m³	NDS: 8h: 5 mg/m³, NDSCh, 15 min, 10 mg/m³	5 mg/m³	8h: 5 mg/m³
Chemical name	Czech Republic	Germany	Hungary	Bulgaria	Ukraine
Oil mist/smoke	PEL: 5 mg/m³ NPK-P: 10 mg/m³	-	-	-	-

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration

(PNEC)

No information available.

8.2. Exposure controls

Engineering controls None under normal use conditions.

Personal protective equipment

Eye/face Protection Hand protection

Wear safety glasses with side shields (or goggles).

Wear protective nitrile rubber gloves, Because specific work environments and material handling practices vary, safety proceduresshould be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even thebest chemically resistant gloves will break down after repeated chemical exposures). Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the

working conditions.

Body protection Respiratory Protection Wear suitable protective clothing.

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. In case of

inadequate ventilation wear respiratory protection.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Prevent product from entering drains. Local authorities should be advised if significant

spillages cannot be contained.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Paste/Gel

Appearance No information available Odor No information available

Color Light Brown Odor Threshold Not applicable

Property Values Remarks • Method

PropertyValuesRemarks • MethorpHNot applicableMelting Point/Freezing PointNot applicable

Boiling point/boiling range

No information available

Flash Point

Flash point COC >150 °C ISO 2592
Flash point PM Not applicable
Evaporation Rate Not applicable
Flammability (solid, gas) Not applicable
Flammability Limits in Air

Upper Flammability limits

Not applicable

Lower Flammability Limit
Vapor pressure @20°C (kPa)

< 0.01

Not applicable

Vapor Density Not applicable

Relative Density

No information available

Water Solubility Negligible

Solubility(ies) Soluble in Solvent Partition Coefficient (n-octanol/water) > 3

Autoignition Temperature

No information available

No information available

No information available

Kinematic Viscosity

Viscosity at 40°C Typical

Viscosity at 100°C Typical

No information available

No information available

No information available

Explosive PropertiesNot applicableOxidizing PropertiesNot applicable

9.2. Other information

Molecular WeightNo information availableVOC Content(%)No information availableDensityNo information availableBulk densityNo information available

Research Octane Number
Sulphur Content
Not applicable
Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Not reactive.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

None under normal use conditions. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Product Information

Germ cell mutagenicity

Product does not present an acute toxicity hazard based on known or supplied information. Used product can contain harmful contaminants.

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system.

Eye Contact Contact with eyes may cause irritation.

Skin Contact Prolonged contact may cause redness and irritation. May cause skin irritation and/or

dermatitis. Product that under high pressure has been forced under the skin, may causae

serious cell damage/death under the skin.

Ingestion Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and

pneumonitis.

None known.

skin corrosion/irritationNone known.

Serious eye damage/eye irritation None known.

sensitization None known.

Carcinogenicity None known.

Reproductive Toxicity None known.

developmental toxicity None known.

Teratogenicity None known.

STOT - single exposure None known.

STOT - repeated exposure None known.

Neurological effects None known.

Target organ effects None known.

aspiration hazard None known.

SECTION 12: Ecological information

12.1. Toxicity

Not harmful to aquatic organisms. Expected LC/EC 50 value >100 mg/l

GREASEWAY HT 2

12.2. Persistence and degradability

Potentially degradable, but will persist in the environment for long periods.

12.3. Bioaccumulative potential

Contain components with potential to bioaccumulate (logPow >3).

12.4. Mobility in soil

Mobility in soil

After release, adsorbs onto soil.

12.5. Results of PBT and vPvB assessment

This product is not, or does not contain, a substance that is a PBT or a vBvP.

12.6. Other adverse effects

An oilfilm may cause physical damage to organisms and disturb the transportation of oxygen in the intermediate zone between air/water or air/soil

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues / Unused Products

Disposal should be in accordance with applicable regional, national and local laws and regulations.

GREASEWAY HT 2

Other information

Provisions for waste transmitters:

Different types of hazardous waste shall not be mixed with each other. Wastes can be mixed if the purpose is to improve safety during disposal or recycling or otherwise is done in a manner acceptable to protect the environment. Waste may be transported professionally only by those who have special permission. Solvent and oil waste under certain given amounts may be transported without special permission, after notification to the County Board. Contact the County Board for further information.

Discharge Instructions:

Packs marked with a skull or environmental hazard symbol and risk phrase 50/53 should always be disposed of as hazardous waste. Other packs should be emptied well before they can be recycled or reconditioned. The contents may need to be disposed of as hazardous waste. Draining is best carried out at room temperature. The pack is placed upside down inclined somewhat, about 10 degrees, the runoff should be in such a way that the lowest point of the pack is the exit. Residual content should be collected and added to the process there the product is used. For steel drums especially the runoff must be at room temperature (min 15 ° C). Wait until the pack is drip dry. Do not reseal the packs after runoff. Note in particular the risks involved when emptying containers containing flammable liquids. Emptied packages should be ventilated in a safe place away from sparks and fire. Residues may cause an explosion. Do not puncture, cut or weld in uncleaned packages, containers or barrels. If possible, packs contained water-soluble product should be rinsed thoroughly (3 times) before emptying. The rinse water should, if possible, be used in the process there the product is used.

Classification of wastes:

Waste transmitters is required to classify the waste. All waste is identified by a six digit EWC code. The codes are listed in the Waste Regulation. The codes for oil waste are based on usage and the base oil. Information about the intended use is given in the safety data sheet, section 1. Oil waste is always hazardous waste. Examples of EWC codes for oil waste:120107: mineral-based machining oils free of halogens130111: Synthetic Hydraulic Oils130105: Non-chlorinated emulsions130208: other engine, gear and lubricating oils

Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

IMDG

14.1UN/ID noNot regulated14.2Proper Shipping NameNot regulated14.3Hazard ClassNot regulated14.4Packing groupNot regulated14.5Marine pollutantNot applicable

14.6 Special Provisions None

14.7 Transport in bulk according to No information available

Annex II of MARPOL 73/78 and the

IBC Code

RID

14.1 UN/ID noNot regulated14.2 Proper Shipping NameNot regulated14.3 Hazard ClassNot regulated14.4 Packing groupNot regulated14.5 environmental hazardNot applicable

14.6 Special Provisions None

<u>ADR</u>

14.1 UN/ID noNot regulated14.2 Proper Shipping NameNot regulated14.3 Hazard ClassNot regulated

14.4 Packing groupNot regulated14.5 environmental hazardNot applicable

14.6 Special Provisions None

ICAO (air)

14.1 UN/ID noNot regulated14.2 Proper Shipping NameNot regulated14.3 Hazard ClassNot regulated14.4 Packing groupNot regulated14.5 environmental hazardNot applicable

14.6 Special Provisions None

IATA

14.1UN/ID noNot regulated14.2Proper Shipping NameNot regulated14.3Hazard ClassNot regulated14.4Packing groupNot regulated14.5environmental hazardNot applicable

14.6 Special Provisions None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations This safety data sheet is created with use of legislation & regulation valid for the European

Union, for example consolidated versions of REACh,1907/2006; CLP, 1272/2008; DPD

1999/45 and national legislation.

Danish PR number: 2237379

International Inventories

Complies **TSCA** Complies **EINECS/ELINCS** Complies **DSL/NDSL** Complies **PICCS** Complies **ENCS IECSC** Complies Complies **AICS** Complies **KECL**

Legend

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances

AICS - Australian Inventory of Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

Full text of R-phrases referred to under sections 2 and 3

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

GREASEWAY HT 2

Full text of H-Statements referred to under sections 2 and 3

H373 - May cause damage to the kidneys/ liver/ eyes/ brain/ respiratory system/ central nervous system through prolonged or repeated exposure if inhaled

H412 - Harmful to aquatic life with long lasting effects

Key or legend to abbreviations and acronyms used in the safety data sheet

vBvP = Very Bioaccumulative and very Pollutant.
PBT = Persistant Bioccumulative Toxic chemical
REACh = Research Evaluation Authorization and Restriction of Chemicals
CLP = Classification, Labelling and Packaging
DPD = Dangerous Preparations Directive
VOC=Volatile Organic Compound

Issue Date 18-Jun-2013

Revision date 03-Mar-2015

Revision Note Indication of changes ***, if applicable.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

End of Safety Data Sheet
