



## Veolia PMT Liquid grease PMTF 17 Fluid grease for rolling and plain bearings subject to high loads

### Advantages for your applications •

- Good water resistance
- High wear protection
- Easy feedability

### Description

Veolia PMT Liquid grease PMTF 17 is a multi-purpose fluid grease based on mineral oil.

It offers good water resistance and corrosion protection even at high temperatures.

### Application

Veolia PMT Liquid grease PMTF 17 is used for the operational lubrication of bearings, guides and seals in the steel industry.

Due to its consistency this fluid grease is suitable for use in Veolia PMT Lubrication Systems.

### Application information

Veolia PMT Liquid grease PMTF 17 is a lubricant especially developed for the Veolia PMT Lubrication Systems. To ensure adequate metering and maintenance-free lubrication, this product is only available in an Veolia PMT Lubrication System.

### Shelf life

Shelf life is approx. 12 months if the product is stored in its unopened original container in a dry and frost-protected place.

### Packaging

- Nova 125ml
- Cartridge 400 g

Unsere Marken: AQUANTIS | BERKEFELD | ELGA | PMT | RWO | Standard Solutions Platform  
Lückenweg 5 | 29227 Celle, Deutschland | Telefon: +49(0)5141 803-0 | Fax: +49(0)5141 803-100 | [veoliawatertech.de@veolia.com](mailto:veoliawatertech.de@veolia.com) | [www.veoliawatertechologies.de](http://www.veoliawatertechologies.de)  
Geschäftsführung: Dr. Christian Ausfelder, Christof Berlin  
Sitz der Gesellschaft: Celle | Registergericht: Lüneburg | Register-Nr.: HRB 200047 | Ust-IdNr.: DE811755553

#### Weitere Standorte:

Lise-Meitner-Straße 4A  
40878 Ratingen  
T +49 (0) 2102 99754-0  
F +49 (0) 2102 99754-89

Bindlacher Straße 4  
95448 Bayreuth  
T +49 (0) 921 150879-0  
F +49 (0) 921 150879-200

Walter-Köhn-Straße 1c  
04356 Leipzig  
T +49 (0) 341 65068-0  
F +49 (0) 341 65068-100

Am Löwengang 3  
74564 Crailsheim  
T +49 (0) 7951 297275-0  
F +49 (0) 7951 297275-75

Gerold-Janssen-Straße 2  
28359 Bremen  
T +49 (0) 421 53705-0  
F +49 (0) 421 53705-440



**Veolia PMT Liquid grease PMTF 17**  
 Fluid grease for rolling and plain bearings subject to high loads

**Product data**

Appearance	transparent
Chemical composition, thickener	aluminium complex soap
Chemical composition, type of oil	mineral oil
Density at 20 °C	approx. 0,88 g/cm <sup>3</sup>
Colour space	brown
Lower service temperature	-20 °C / -4 °F
Upper service temperature	130 °C / 266 °F
Kinematic viscosity of the base oil, DIN 51562, 40 °C	approx. 220 mm <sup>2</sup> /s
Kinematic viscosity, DIN 51562, 100 °C	approx. 19 mm <sup>2</sup> /s
Speed factor (rpm x dm)	approx. 300 000
NLGI grade, DIN 51818	0
Texture	homogeneous
Texture	f brous
Drop point, DIN ISO 2176	>= 210 °C

Unsere Marken: AQUANTIS | BERKEFELD | ELGA | PMT | RWO | Standard Solutions Platform

Lückenweg 5 | 29227 Celle, Deutschland | Telefon: +49(0)5141 803-0 | Fax: +49(0)5141 803-100 | [veoliawatertech.de@veolia.com](mailto:veoliawatertech.de@veolia.com) | [www.veoliawatertech.de](http://www.veoliawatertech.de)

Geschäftsführung: Dr. Christian Ausfelder, Christof Berlin

Sitz der Gesellschaft: Celle | Registergericht: Lüneburg | Register-Nr.: HRB 200047 | Ust-IdNr.: DEB11755553

*Weitere Standorte:*

Lise-Meitner-Straße 4A  
 40878 Ratingen  
 T +49 (0) 2102 99754-0  
 F +49 (0) 2102 99754-89

Bindlacher Straße 4  
 95448 Bayreuth  
 T +49 (0) 921 150879-0  
 F +49 (0) 921 150879-200

Walter-Köhn-Straße 1c  
 04356 Leipzig  
 T +49 (0) 341 65068-0  
 F +49 (0) 341 65068-100

Am Löwengang 3  
 74564 Crailsheim  
 T +49 (0) 7951 297275-0  
 F +49 (0) 7951 297275-75

Gerold-Janssen-Straße 2  
 28359 Bremen  
 T +49 (0) 421 53705-0  
 F +49 (0) 421 53705-440