

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma High speed grease SF08

Version	Revision Date:	Date of last issue: 27.06.2019	Print Date:
1.9	18.11.2019	Date of first issue: 20.01.2015	18.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : perma High speed grease SF08

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Grease

Recommended restrictions
on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

perma-tec GmbH & Co. KG
Hammelburger Str. 21
97717 EUERDORF
GERMANY
Tel: +49 9704 609-0
Fax: +49 9704 609-50
info@perma-tec.com

E-mail address of person
responsible for the SDS : msds@perma-tec.com

National contact : H-T-L perma UK
6 – 9 The Square
Stockley Park
UXBRIDGE
MIDDLESEX UB11 1FW
UNITED KINGDOM
Phone: +44 20 8622 3076
Fax: +44 20 8622 3200
www.perma-tec.com

1.4 Emergency telephone number

+49 9704 609-99 (Mo-Do 08:00-16:30, Fr 08:00-12:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma High speed grease SF08

Version	Revision Date:	Date of last issue: 27.06.2019	Print Date:
1.9	18.11.2019	Date of first issue: 20.01.2015	18.11.2019

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling

EUH210 Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Synthetic hydrocarbon oil
special calcium soap

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
1,3,4-Thiadiazolidine- 2,5-dithione, reaction products with hydro- gen peroxide and tert- dodecanethiol	939-692-2 01-2119983498-16- XXXX	Aquatic Chronic3; H412		$\geq 1 - < 2.5$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
Wash off with soap and water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma High speed grease SF08

Version	Revision Date:	Date of last issue: 27.06.2019	Print Date:
1.9	18.11.2019	Date of first issue: 20.01.2015	18.11.2019

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
Do not induce vomiting without medical advice.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : None known.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Fire may cause evolution of:
Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)
Sulphur oxides

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.
- Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Evacuate personnel to safe areas.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma High speed grease SF08

Version	Revision Date:	Date of last issue: 27.06.2019	Print Date:
1.9	18.11.2019	Date of first issue: 20.01.2015	18.11.2019

(dust).
Do not breathe vapours, aerosols.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Clean up promptly by sweeping or vacuum.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma High speed grease SF08

Version 1.9 Revision Date: 18.11.2019 Date of last issue: 27.06.2019
Date of first issue: 20.01.2015

Print Date:
18.11.2019

Substance name	End Use	Exposure routes	Potential health effects	Value
1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-dodecanethiol	Workers	Inhalation	Long-term systemic effects	4.408 mg/m ³
	Workers	Skin contact	Long-term systemic effects	6.25 mg/kg bw/day
bis(4-(1,1,3,3-tetramethylbutyl)phenyl)amine	Workers	Inhalation	Long-term systemic effects	4.11 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1.17 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-dodecanethiol	Fresh water	0.041 mg/l
	Marine water	0.0041 mg/l
	Intermittent use/release	0.41 mg/l
	Microbiological Activity in Sewage Treatment Systems	8000 mg/l
	Fresh water sediment	380.62 mg/kg
bis(4-(1,1,3,3-tetramethylbutyl)phenyl)amine	Marine sediment	38.06 mg/kg
	Soil	308.98 mg/kg
	Oral	6.67 mg/kg
	Fresh water	0.00002 µg/l
	Marine water	0.000002 µg/l
	Fresh water sediment	0.00467 mg/kg
	Marine sediment	0.000467 mg/kg
	Soil	0.000934 mg/kg

8.2 Exposure controls

Engineering measures

none

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber
Protective index : Class 1

Remarks : For prolonged or repeated contact use protective gloves. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The break through time depends amongst other things on the material, the thickness and the type of glove

